

# CENTER 317

# HUMIDITY TEMPERATURE METER

(DEW POINT & WET BULB)



CE

## Feature:

- Dew Point and Wet Bulb temperature Measurement.
- Fast response.
- Auto shut off for Battery Saving.
- MAX/MIN Function.
- Dual displays: Primary display for Humidity; Secondary displays for temperature.

**CENTER**®

# CENTER 317 HUMIDITY TEMPERATURE METER

## SPECIFICATIONS

### Measurement Range:

Temperature:  $-20^{\circ}\text{C}\sim 60^{\circ}\text{C}$ ;  $-4^{\circ}\text{F}\sim 140^{\circ}\text{F}$

Humidity: 0%RH~99%RH

**Resolution:** 0.1°C/0.1°F/0.1%RH

### Accuracy:

Temperature:  $\pm 0.8^{\circ}\text{C}$ ,  $1.6^{\circ}\text{F}$

Humidity:  $\pm 2.5\%RH$

**Sampling Rate:** 2.5 times/sec

### Humidity Sensor:

Electronic capacitance polymer film sensor.

**Battery Type:** 1.5V AA size battery x 4

**Operating Condition:**  $0^{\circ}\text{C}$  to  $40^{\circ}\text{C}$  (<80%RH)

**Dimensions:** 210×65×43mm

**Accessories:** Batteries, Instruction Manual




LED Back Light

1:1 Size



## Dual Display



Primary display for Humidity;  
Secondary displays for temperature.

Pull Up  
Sensor  
Protector.



33%RH / 75%RH  
Humidity Standard (OPTIONAL)

\* The specifications and other information in this catalogue are subject to change without prior notice.

**CENTER**<sup>®</sup>  
**CENTER TECHNOLOGY CORP.**

4/F., NO.415, Jung-Jeng Rd., 238 Shu-Lin, Taipei, Taiwan  
TEL: 886-2-26763926 E-Mail: center@centertek.com  
FAX: 886-2-26763925 http://www.centertek.com

Distributed by:

Importør:  
Impex Produkter AS  
Gamle Drammensvei 107  
1363 HØVIK  
Tel. 22 32 77 20  
info@impex.no  
www.impex.no