

Diligence EV N2000 Series Data Loggers



Comark's Diligence EV range of data loggers provides a complete solution for the measurement of temperature, humidity or mA current.

The loggers are stand-alone, lightweight and small enough to be used almost anywhere that regular monitoring is required, reducing the need for manual checks and improving the accuracy of your information.

Use with EV Software to program logger tasks, download and analyse data, keeping permanent records to meet the requirements of industry regulations.

Housed in a robust case and waterproof to IP67 standards, the Diligence EV range includes multi-sensor models, capable of simultaneously monitoring several temperature locations.

Features

- LCD display screen allows instant checks of current readings and alarms
- Large memory capacity with wraparound for continual real-time and historic data collection no forgotten readings, just log data and download
- Alarm indication lights instantly warn of potentially unsafe conditions allowing instant corrective action
- Water and dustproof sealed to IP67 standards for long life expectancy and accuracy
- Lumberg connector provides secure connection of a wide range of Comark probes-types K, T or thermistor (model dependent)
- Battery life up to five years enabling logging assignments over extended periods
- Models with external probes are ideal for monitoring fridges and freezers
- Models with built in sensor are suitable for chillers, storage and transport applications
- Model measuring mA current can be easily connected into the control loop and programmed to measure a wide range of parameters for process and building management checks such as pressure, pH, airflow, dissolved oxygen and many more
- UKAS Calibration Certificates available on most models
- Software available free of charge, download from product pages on www.comarkinstruments.com.

Warranty

All Comark instruments have a minimum one year warranty unless otherwise stated. The warranty for temperature probes is six months and all other probes are unwarranted because the conditions of use are beyond our control. The Comark Warranty covers manufacturing defects and component failure and applies worldwide. In line with our policy of continuous development, we reserve the right to alter any product specification without notice. Comark has an accredited UKAS (NIST equivalent) calibration laboratory for temperature and humidity measurement and offers full service and recalibration facilities.

Comark Instruments is committed to providing quality and affordable products to the food service industry. Our thermometers and humidity testers bring speed, accuracy and reliability to the transport, testing and storing of food under HACCP guidelines. A large variety of products, well-trained staff, and a commitment to customer satisfaction mean you can come to us for answers to all your temperature measurement needs!



Comark Instruments

52 Hurricane Way
Norwich, Norfolk, NR6 6JB
United Kingdom
Tel: +44 (0) 207 942 0712
Fax: +44 (0) 207 942 0714
Email: sales@comarkinstruments.com

Comark Instruments

P.O. Box 500
Beaverton, OR 97077, USA
Tel: +1 (503) 643 5204
Toll Free: (800) 555 6658
Fax: +1 (503) 627 5311
Email: sales@comarkusa.com



Diligence Ev

Comark N2000 Series

Data Loggers

Specifications

Sensor Type	
N2011, N2012, N2013	Thermistor
N2014	Type K or Type T thermocouple
Connector	Lumberg
Measurement Range	
N2011, N2012 internal sensor	-40°C to +70°C / -40°F to +158°F
N2012 external sensor	-40°C to +150°C / -40°F to +302°F
N2013 temperature	-20°C to +60°C / -4°F to +140°F
N2013 humidity	0 to 97% RH non condensing
N2014 - Type K	-200°C to +1372°C / -392°F to +2500°F
N2014 - Type T	-200°C to +400°C / -392°F to +752°F
N2014 - Thermistor	-40°C to +70°C / -40°F to +158°F
N2015	4 to 20mA
Scales	
Temperature	°C and °F
Humidity	RH or DP
Displayed Resolution	
Temperature	0.1° (1° below -100°C, -148°F and above +1000°C or °F)
Humidity	0.1% RH
N2014	0.2°
N2015 only	4 digits 1 decimal place (software allows 0 to 4 decimals in logged data)
Internal Accuracy at +20°C/+65°F ambient	
N2014	±0.5°C +0.5% (±0.9°F +0.5%) of reading over the range of -80°C to thermocouple limit
N2015	±0.3% of full scale
Memory	32K
1 channel	16000 samples
2 channels	8000 samples
3 channels	5300 samples
4 channels	4000 samples
5 channels	3200 samples
Logging Frequency	Programmable between 1 second and 99 hours,
N2014	2 seconds to 99 hours
Communications	Via infrared interface
Download Time	3 minutes per 10,000 readings (typical)
Ambient Storage	-40°C to +70°C / -40°F to +158°F
Battery Type	1 x AA size 3.6V replaceable lithium battery
Case Material	ABS
Environmental Protection	IP67, EN 60529, IEC 529

For more details fo the Diligence WiFi range, please see www.comarkinstruments.com

* Software selection of decimals will affect recorded values, e.g. selection of 0 decimals = 1 value of ±32000 and a selection of 4 decimals = a value of ±3.2000

All rights reserved. Data subject to alteration without notice. All trademarks are the property of their respective owners. Modification of this document is not permitted without written permission from Comark Instruments.

© 2017 Comark Instruments Part No. 20362-2

The Professionals' Choice