KERN FFN3K1IPM



All-round bench scale, protected by stainless steel and IP65 rating, now also with EC type approval [M]



Measuring system	
Adjustment options:	External calibration
Linearity:	1 g
Readability [d]:	1 g
Recommended adjusting weight:	3 kg (M3)
Repeatability:	1 g
Resolution:	3000
Stabilisation time under laboratory conditions:	2 s
Tare range:	-2,999 kg
Warm up time:	10 min
Weighing capacity [Max]:	3 kg
Weighing system:	Strain gauge
Weighing units:	g kg

Display		
Display digit height:	2,500 cm	

Technical data about verification	
Minimum load [Min]:	20 g
Periodic Verification for Italy:	969-112
Verification approval conforming to 2014/31/EU:	yes
Verification by KERN possible:	yes
Verification class:	III
Verification value [e]:	1 g

Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	-10 °C
Minimum humidity:	0 %

Power supply	
Charging time:	12 h
Input voltage:	110 V - 230 V AC
Mains adapter/adapter included:	CH EURO UK US

n/a:	Mains adapter external
Power supply	
Operating time (Backlight off):	50 h
Operating time (Backlight on):	30 h
Comples	

Adjustment at the location of installation: 961-247

DAkkS Certificate:	963-127
Verification:	965-227

Category	
Brand:	KERN
Category:	Balances
Product Group:	Bench scale

24 h
304 x 403 x 206 mm
4,722 kg
4,010 kg
Parcel service
2800

Construction	
Dimensions housing (WxDxH):	230 x 300 x 130 mm
Level indicator:	yes
Material weighing plate:	stainless steel
Overall dimensions mounted (WxDxH):	230 x 300 x 130 mm
Revolving screw feet:	yes
Weighing surface (WxD):	230 x 190 mm

KERN FFN3K1IPM



All-round bench scale, protected by stainless steel and IP65 rating, now also with EC type approval [M]

Piktogramme STANDARD Lacu B Lacu Multi DMS 1 DAY OPTION DAKKS +3 DAYS FACTORY