## KERN IFB6K1DM



High-resolution scale in heavy version with EC type approval [M], now also up to [Max] 600 kg



	4
Adjustment options:	External calibration
Linearity:	1 g   2 g
Load cell connection:	4-Leiter
Readability [d]:	1 g   2 g
Recommended adjusting weight:	6 kg (F2)
Repeatability:	1 g   2 g
Resolution:	3 3.000
Stabilisation time under laboratory conditions:	2 s
Tare range:	-6 kg

Measuring system

Stabilisation time under laboratory conditions:	2 s
Tare range:	-6 kg
Warm up time:	10 min   10 min
Weighing capacity [Max]:	3 kg   6 kg
Weighing system:	Strain gauge
Weighing units:	kg
Display	
Display digit height:	5,200 cm

Technical data about verification	
Minimum load [Min]:	20 g   40 g
Periodic Verification for Italy:	969-112
Verification approval conforming to 2014/31/EU:	yes
Verification by KERN possible:	yes
Verification class:	III
Verification value [e]:	1 g   2 g
Counting	
Counting resolution:	30000

Counting resolution:	30000
Mininum piece weight at piece counting (Laboratory:	200 mg
Mininum piece weight at piece	2 g

Functions	
Counting function:	yes
Function to save totals:	yes
Percentage determination:	yes
Vibration-free weighing (Animal weighing program):	yes
Weighing with tolerance range:	yes
Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	-10 °C
Minimum humidity:	0 %
Power supply	
Charging time:	12 h
Input voltage:	100 V - 240 V 50 / 60 Hz
Mains adapter/adapter included:	CH EURO UK US
n/a:	Mains adapter external
Power supply	
Operating time (Backlight off):	35 h
Operating time (Backlight off): Operating time (Backlight on):	35 h 8 h
Operating time (Backlight on):	8 h Rchrg. battery optional
Operating time (Backlight on): Rechargeable battery:	8 h Rchrg. battery optional (factory)
Operating time (Backlight on): Rechargeable battery: Service	8 h Rchrg. battery optional (factory)
Operating time (Backlight on): Rechargeable battery: Service Adjustment at the location of installation	8 h Rchrg. battery optional (factory) : 961-248
Operating time (Backlight on): Rechargeable battery: Service Adjustment at the location of installation DAkkS Certificate:	8 h Rchrg. battery optional (factory) : 961-248 963-128
Operating time (Backlight on): Rechargeable battery: Service Adjustment at the location of installation DAkkS Certificate: Verification:	8 h Rchrg. battery optional (factory) : 961-248 963-128
Operating time (Backlight on): Rechargeable battery: Service Adjustment at the location of installation DAkkS Certificate: Verification: Category Brand:	8 h Rchrg. battery optional (factory) : 961-248 963-128 965-228
Operating time (Backlight on): Rechargeable battery: Service Adjustment at the location of installation DAkkS Certificate: Verification: Category	8 h Rchrg. battery optional (factory) : 961-248 963-128 965-228 KERN
Operating time (Backlight on): Rechargeable battery: Service Adjustment at the location of installation DAkkS Certificate: Verification: Category Brand: Category:	8 h Rchrg. battery optional (factory) :961-248 963-128 965-228 KERN Balances
Operating time (Backlight on): Rechargeable battery: Service Adjustment at the location of installation DAkkS Certificate: Verification: Category Brand: Category: Product Group: Packaging & shipping	8 h Rchrg. battery optional (factory) :961-248 963-128 965-228 KERN Balances
Operating time (Backlight on): Rechargeable battery: Service Adjustment at the location of installation DAkkS Certificate: Verification: Category Brand: Category: Product Group: Packaging & shipping Delivery:	8 h Rchrg. battery optional (factory) : 961-248 963-128 965-228 KERN Balances Industiral scale 24 h
Operating time (Backlight on): Rechargeable battery: Service Adjustment at the location of installation DAkkS Certificate: Verification: Category Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH):	8 h Rchrg. battery optional (factory) :961-248 963-128 965-228 KERN Balances Industiral scale 24 h 415 x 715 x 240 mm
Operating time (Backlight on): Rechargeable battery: Service Adjustment at the location of installation DAkkS Certificate: Verification: Category Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight:	8 h Rchrg. battery optional (factory) :961-248 963-128 965-228 KERN Balances Industiral scale 24 h 415 x 715 x 240 mm 7,200 kg
Operating time (Backlight on): Rechargeable battery: Service Adjustment at the location of installation DAkkS Certificate: Verification: Category Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH):	8 h Rchrg. battery optional (factory) :961-248 963-128 965-228 KERN Balances Industiral scale 24 h 415 x 715 x 240 mm

counting (Normal): KERN & SOHN GmbH · Ziegelei 1 · 72336 Balingen · Germany · Tel. +49–(0)7433 - 99 33-0 · www.kern-sohn.com

# KERN IFB6K1DM

High-resolution scale in heavy version with EC type approval [M], now also up to [Max] 600 kg



### Construction

Cable length of display device:	3 m
Casing material:	Plastic
Dimensions of display device (WxDxH):	250 x 160 x 58 mm
Dimensions of weighing plate (WxDxH):	300 x 240 x 110 mm
of stand:	3,300 m
Level indicator:	yes
Material weighing plate:	stainless steel
Overall dimensions mounted (WxDxH):	460 x 240 x 360 mm
Revolving screw feet:	yes
Wall mount:	yes
Weighing surface (WxD):	300 x 240 mm

#### Piktogramme

#### STANDARD



OPTION

DAkkS +3 days

#### FACTORY

