

## TES-1350A Sound Level Meter



### FEATURES

- 0.1dB Resolution
- Maximum hold function
- AUX OUTPUT JACKS

**Importør:**  
**Impex Produkter AS**  
**Gamle Drammensvei 107**  
**1363 HØVIK**  
**Tel. 22 32 77 20**  
**info@impex.no**  
**www.impex.no**



### SPECIFICATION

|                     |  |
|---------------------|--|
| Standard applied    | IEC 651 Type2  |
| Range               | A LO (Low) - Weighting: 35- 100dB<br>A HI (High) - Weighting: 65-130dB<br>C LO (Low) - Weighting: 35- 100dB<br>C HI (High) - Weighting: 65-130dB |
| Resolution          | 0.1dB  |
| Frequency Range     | 31.5Hz to 8KHz   |
| Accuracy            | ±2dB   |
| Dynamic Range       | 65dB   |
| Frequency Weighting | A 、 C  |
| Time Weighting      | Slow & Fast  |
| Maximum Hold        | Decay < 1dB/3min   |
| Microphone          | Electret condenser microphone  |
| Calibration         | Electrical calibration by using the internal oscillator<br>(1KHz sine Wave at 94dB)  |
| Auxiliary Output    | AC conditioned, 0.65Vrms corresponding to<br>each range step, impedance: 600 W<br>DC conditioned, 10mV/dB (nominally)                            |
| Operating Condition | 0°C to 40 °C < 80% R. H.   |
| Storage Condition   | -10°C to 60 °C < 70% R.H.  |
| Display             | 3 1/2 digitals   |
| Power Supply        | one 9V battery   |
| Size                | 240mm(L)x68mm(W)x25mm(H)   |
| Weight              | 210g   |
| Accessories         | Instruction Manual, 9V Battery, Carrying Case,<br>Screwdriver, Windscreen.   |