

KERN PCB 1000-2

The standard in the laboratory



Measuring system

Adjustment options:	External calibration
Linearity:	30 mg
Minimum weight (USP):	20 g
Readability [d]:	10 mg
Recommended adjusting weight:	1 kg (F1)
Repeatability:	10 mg
Resolution:	100000
Stabilisation time under laboratory conditions:	3 s
Warm up time:	2 h
Weighing capacity [Max]:	1 kg
Weighing system:	Strain gauge
Weighing units:	ct dwt g gn lb mo oz oz t l (HK) tl (Tw) tol

Display

Display digit height:	2,100 cm
-----------------------	----------

Counting

Counting resolution:	50000
Minimum piece weight at piece counting (Laboratory):	20 mg
Minimum piece weight at piece counting (Normal):	200 mg

Functions

Counting function:	yes
Percentage determination:	yes
Suspended weighing:	Hook
Vibration-free weighing (Animal weighing program):	yes

Environmental conditions

Maximum humidity:	80 %
Maximum operating temperature:	35 °C
Minimum ambient temperature:	5 °C

Power supply

Battery:	9 V Block
Charging time:	8 h
Input voltage:	220 V -240 V AC; 50Hz 60Hz
Mains adapter/adapter included:	CH EURO UK US

n/a: Mains adapter external

Power supply

Operating time:	20 h
Operating time (Backlight off):	48 h
Operating time (Backlight on):	24 h
Rechargeable battery:	Rchrg. battery optional

Service

DAkkS Certificate:	963-127
--------------------	---------

Category

Brand:	KERN
Category:	Balances
Product Group:	Precision balance

Packaging & shipping

Delivery:	24 h
Dimensions packaging (WxDxH):	232 x 357 x 180 mm
Gross weight:	1,770 kg
Net weight:	1,254 kg
Shipping method:	Parcel service

Construction

Casing material:	Plastic
Dimensions housing (WxDxH):	163 x 245 x 85 mm
Level indicator:	yes
Material weighing plate:	stainless steel
Weighing surface (WxD):	130 x 130 mm

KERN PCB 1000-2

The standard in the laboratory



Piktogramme

STANDARD



OPTION

