

KERN HCN50K100IP

The handy scale for higher loads

KERN[®]



Measuring system

| | |
|---|----------------------|
| Adjustment options: | External calibration |
| Linearity: | 200 g |
| Precision (of [Max]): | 0,500 % |
| Readability [d]: | 100 g |
| Recommended adjusting weight: | 50 kg (M2) |
| Repeatability: | 100 g |
| Resolution: | 500 |
| Stabilisation time under laboratory conditions: | 2 s |
| Warm up time: | 10 min |
| Weighing capacity [Max]: | 50 kg |
| Weighing system: | Strain gauge |
| Weighing units: | kg lb N |

Display

| | |
|-----------------------|----------|
| Display digit height: | 1,200 cm |
|-----------------------|----------|

Functions

| | |
|---------------------|-----|
| Data hold function: | yes |
|---------------------|-----|

Environmental conditions

| | |
|--------------------------------|-------|
| Maximum humidity: | 80 % |
| Maximum operating temperature: | 35 °C |
| Minimum ambient temperature: | 5 °C |

Power supply

| | |
|-----------------|------------|
| Battery: | 2x1.5 V AA |
| Operating time: | 200 h |

Service

Adjustment at the location of installation: 961-248

| | |
|--------------------|----------|
| DAkkS Certificate: | 963-128H |
|--------------------|----------|

Category

| | |
|----------------|---------------|
| Brand: | KERN |
| Category: | Balances |
| Product Group: | Hanging scale |

Packaging & shipping

| | |
|-------------------------------|-------------------|
| Delivery: | 24 h |
| Dimensions packaging (WxDxH): | 155 x 220 x 75 mm |
| Gross weight: | 1,145 kg |
| Net weight: | 800 g |
| Shipping method: | Parcel service |

KERN HCN50K100IP

The handy scale for higher loads



Construction

| | |
|-----------------------------|------------------|
| Casing material: | stainless steel |
| Dimensions housing (WxDxH): | 90 x 45 x 180 mm |

Piktogramme

STANDARD



OPTION

