KERN WTB30K-2NM



Ideal for food industry, thanks to its IP65 protection and special checkweighing display, now also with EC type approval [M]



Measuring system	
Adjustment options:	External calibration
Linearity:	10 g
Readability [d]:	10 g
Recommended adjusting weight:	30 kg (M1)
Repeatability:	10 g
Resolution:	3000
Stabilisation time under laboratory conditions:	2 s
Tare range:	-29,990 kg
Warm up time:	10 min
Weighing capacity [Max]:	30 kg
Weighing system:	Strain gauge
Weighing units:	g kg

Display	
Additional Display possible:	yes
Display digit height:	2,500 cm

Technical data about verification	
Minimum load [Min]:	200 g
Periodic Verification for Italy:	969-112
Verification approval conforming to 2014/31/EU:	yes
Verification by KERN possible:	yes
Verification class:	III
Verification value [e]:	10 g
Functions	

yes

Weighing with tolerance range:

Environmental conditions		
Maximum humidity:	80 %	
Maximum operating temperature:	40 °C	
Minimum ambient temperature:	-10 °C	
Minimum humidity:	0 %	
Power supply		
Charging time:	12 h	
Input voltage:	110 V - 230 V AC	
Mains adapter/adapter included:	CH EURO UK US	
n/a:	Mains adapter external	
Power supply		
Operating time (Backlight off):	50 h	
Operating time (Backlight on):	30 h	
Rechargeable battery:	Rchrg. battery optional - intern	
Service		
Adjustment at the location of installation: 961-248		
DAkkS Certificate:	963-128	
Verification:	965-228	
Category		
Brand:	KERN	
Category:	Balances	
Packaging & shipping		
Delivery:	24 h	
Dimensions packaging (WxDxH):	400 x 340 x 195 mm	
Gross weight:	4,048 kg	
Net weight:	3,134 kg	
Shipping method:	Parcel service	
Construction		
Casing material:	Plastic	
Dimensions housing (WxDxH):	285 x 315 x 128 mm	
Dimensions of weighing plate (WxDxH):	260 x 200 x 16,2 mm	
Level indicator:	yes	

Material weighing plate:

Revolving screw feet:

Weighing surface (WxD):

(WxDxH):

Overall dimensions mounted

stainless steel

260 x 200 mm

yes

285 x 315 x 128 mm

KERN WTB30K-2NM



Ideal for food industry, thanks to its IP65 protection and special checkweighing display, now also with EC type approval [M]

Piktogramme STANDARD Lack Standard Tol IP65 Multi DMS 1 DAY OPTION DAKKS ACCU +3 DAYS FACTORY