

KERN WTB6K-3N



Ideal for food industry, thanks to its IP65 protection and special checkweighing display, now also with EC type approval [M]



Measuring system

| | |
|---|----------------------|
| Adjustment options: | External calibration |
| Linearity: | 2 g |
| Readability [d]: | 1 g |
| Recommended adjusting weight: | 6 kg (M1) |
| Repeatability: | 1 g |
| Resolution: | 6000 |
| Stabilisation time under laboratory conditions: | 2 s |
| Tare range: | -5,999 kg |
| Warm up time: | 30 min |
| Weighing capacity [Max]: | 6 kg |
| Weighing system: | Strain gauge |
| Weighing units: | kg |

Display

| | |
|------------------------------|----------|
| Additional Display possible: | yes |
| Display digit height: | 2,500 cm |

Functions

| | |
|--------------------------------|-----|
| Weighing with tolerance range: | yes |
|--------------------------------|-----|

Environmental conditions

| | |
|--------------------------------|--------|
| Maximum humidity: | 80 % |
| Maximum operating temperature: | 40 °C |
| Minimum ambient temperature: | -10 °C |
| Minimum humidity: | 0 % |

Power supply

| | |
|---------------------------------|------------------|
| Charging time: | 12 h |
| Input voltage: | 110 V - 230 V AC |
| Mains adapter/adaptor included: | CH EURO UK US |

| | |
|------|------------------------|
| n/a: | Mains adapter external |
|------|------------------------|

Power supply

| | |
|---------------------------------|----------------------------------|
| Operating time (Backlight off): | 50 h |
| Operating time (Backlight on): | 30 h |
| Rechargeable battery: | Rchrg. battery optional - intern |

Service

Adjustment at the location of installation: 961-248

| | |
|--------------------|---------|
| DAkkS Certificate: | 963-128 |
|--------------------|---------|

Category

| | |
|----------------|-------------|
| Brand: | KERN |
| Category: | Balances |
| Product Group: | Bench scale |

Packaging & shipping

| | |
|-------------------------------|--------------------|
| Delivery: | 24 h |
| Dimensions packaging (WxDxH): | 400 x 345 x 200 mm |
| Gross weight: | 4,036 kg |
| Net weight: | 3,115 kg |
| Shipping method: | Parcel service |

Construction

| | |
|---------------------------------------|---------------------|
| Casing material: | Plastic |
| Dimensions housing (WxDxH): | 285 x 315 x 128 mm |
| Dimensions of weighing plate (WxDxH): | 260 x 200 x 16,2 mm |
| Level indicator: | yes |
| Material weighing plate: | stainless steel |
| Overall dimensions mounted (WxDxH): | 285 x 315 x 128 mm |
| Revolving screw feet: | yes |
| Weighing surface (WxD): | 260 x 200 mm |

KERN WTB6K-3N



Ideal for food industry, thanks to its IP65 protection and special checkweighing display, now also with EC type approval [M]

Piktogramme

STANDARD



OPTION



FACTORY

