KERN IFB60K-3L



High-resolution scale in heavy version with EC type approval [M], now also up to [Max] 600 kg



Measurir	na ev	vetam
Measuri	iyəy	Storn

weasuring system		
Adjustment options:	External calibration	
Linearity:	8 g	
Load cell connection:	4-Leiter	
Readability [d]:	2 g	
Recommended adjusting weight:	60 kg (F2)	
Repeatability:	2 g	
Resolution:	30000	
Stabilisation time under laboratory conditions:	2 s	
Tare range:	-60 kg	
Warm up time:	2 h	
Weighing capacity [Max]:	60 kg	
Weighing system:	Strain gauge	
Weighing units:	kg	
Display		
Display digit height:	5,200 cm	
Counting		
Counting Counting resolution:	30000	
	30000 2 g	
Counting resolution: Mininum piece weight at piece		
Counting resolution: Mininum piece weight at piece counting (Laboratory: Mininum piece weight at piece	2 g	
Counting resolution: Mininum piece weight at piece counting (Laboratory: Mininum piece weight at piece counting (Normal):	2 g	
Counting resolution: Mininum piece weight at piece counting (Laboratory: Mininum piece weight at piece counting (Normal): Functions	2 g 20 g	
Counting resolution: Mininum piece weight at piece counting (Laboratory: Mininum piece weight at piece counting (Normal): Functions Counting function:	2 g 20 g yes	
Counting resolution: Mininum piece weight at piece counting (Laboratory: Mininum piece weight at piece counting (Normal): Functions Counting function: Function to save totals:	2 g 20 g yes yes	

Environmental conditions		
Maximum humidity:	80 %	
Maximum operating temperature:	40 °C	
Minimum ambient temperature:	-10 °C	
Minimum humidity:	0 %	
Power supply		
Charging time:	12 h	
Input voltage:	100 V - 240 V 50 / 60 Hz	
Mains adapter/adapter included:	CH EURO UK US	
n/a:	Mains adapter external	
Power supply		
Operating time (Backlight off):	35 h	
Operating time (Backlight on):	8 h	
Rechargeable battery:	Rchrg. battery optional	
	(factory)	
Service		
Adjustment at the location of installation	on:961-249	
DAkkS Certificate:	963-129	
Category		
Category Brand:	KERN	
	KERN Balances	
Brand:		
Brand: Category:	Balances	
Brand: Category: Product Group:	Balances	
Brand: Category: Product Group: Packaging & shipping	Balances Industiral scale	
Brand: Category: Product Group: Packaging & shipping Delivery:	Balances Industiral scale 24 h	
Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH):	Balances Industiral scale 24 h 555 x 930 x 215 mm	
Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight:	Balances Industiral scale 24 h 555 x 930 x 215 mm 15,900 kg	
Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight:	Balances Industiral scale 24 h 555 x 930 x 215 mm 15,900 kg 13,700 kg	
Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method:	Balances Industiral scale 24 h 555 x 930 x 215 mm 15,900 kg 13,700 kg	
Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction	Balances Industiral scale 24 h 555 x 930 x 215 mm 15,900 kg 13,700 kg Parcel service	
Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Casing material: Dimensions of display device	Balances Industiral scale 24 h 555 x 930 x 215 mm 15,900 kg 13,700 kg Parcel service 3 m	
Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Casing material: Dimensions of display device (WxDxH): Dimensions of weighing plate	Balances Industiral scale 24 h 555 x 930 x 215 mm 15,900 kg 13,700 kg Parcel service 3 m Plastic	
Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Casing material: Dimensions of display device (WxDxH):	Balances Industiral scale 24 h 555 x 930 x 215 mm 15,900 kg 13,700 kg Parcel service 3 m Plastic 250 x 160 x 58 mm 500 x 400 x 130 mm	
Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Casing material: Dimensions of display device (WxDxH): Dimensions of weighing plate (WxDxH):	Balances Industiral scale 24 h 555 x 930 x 215 mm 15,900 kg 13,700 kg Parcel service 3 m Plastic 250 x 160 x 58 mm 500 x 400 x 130 mm 60 cm	
Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Casing material: Dimensions of display device (WxDxH): Dimensions of weighing plate (WxDxH): of stand: Level indicator:	Balances Industiral scale 24 h 555 x 930 x 215 mm 15,900 kg 13,700 kg Parcel service 3 m Plastic 250 x 160 x 58 mm 500 x 400 x 130 mm	
Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Casing material: Dimensions of display device (WxDxH): Dimensions of weighing plate (WxDxH): of stand:	Balances Industiral scale 24 h 555 x 930 x 215 mm 15,900 kg 13,700 kg Parcel service 3 m Plastic 250 x 160 x 58 mm 500 x 400 x 130 mm 60 cm yes	
Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Casing material: Dimensions of display device (WxDxH): Dimensions of weighing plate (WxDxH): of stand: Level indicator: Material weighing plate:	Balances Industiral scale 24 h 555 x 930 x 215 mm 15,900 kg 13,700 kg Parcel service 3 m Plastic 250 x 160 x 58 mm 500 x 400 x 130 mm 60 cm yes stainless steel	

KERN IFB60K-3L

KERN

High-resolution scale in heavy version with EC type approval [M], now also up to [Max] 600 kg

Revolving screw feet:	yes
Wall mount:	yes
Weighing surface (WxD):	500 x 400 mm

Piktogramme

STANDARD



OPTION

DAkkS +3 Days

FACTORY

8	D⁄A	III)	Μ
BT 2.0	ANALOG	ACCU	+3 DAYS