## KERN SXS30K-2LM



Stainless steel platform scale with stainless steel IP68 display and EC type approval [M]



Measuring system					
Adjustment options:	External calibration				
Linearity:	5g 10g				
Load cell connection:	6-Leiter				
Readability [d]:	5 g   10 g				
Recommended adjusting weight:	30 kg (M1)				
Repeatability:	5 g   10 g				
Resolution:	3 3.000				
Stabilisation time under laboratory conditions:	2 s				
Tare range:	-30 kg				
Warm up time:	10 min   10 min				
Weighing capacity [Max]:	15 kg   30 kg				
Weighing system:	Strain gauge				
Weighing units:	kg				
Display					
Display digit height:	5,500 cm				
Technical data about verification					
Minimum load [Min]:	100 g   200 g				
Periodic Verification for Italy:	969-112				
Verification approval conforming to 2014/31/EU:	yes				
Verification by KERN possible:	yes				
Verification class:	III				
Verification value [e]:	5 g   10 g				
Counting					
Counting resolution:	30000				
Mininum piece weight at piece counting (Laboratory:	1 g				
Mininum piece weight at piece	10 g				
counting (Normal):	- 3				

Functions				
Counting function:	yes			
Data hold function:	yes			
Help function on the display:	yes			
Peak function:	yes			
PRE-TARE function:	yes			
Vibration-free weighing (Animal	yes			
weighing program):				
Weighing with tolerance range:	yes			
Environmental conditions				
Maximum humidity:	80 %			
Maximum operating temperature:	40 °C			
Minimum ambient temperature:	-10 °C			
Minimum humidity:	0 %			
Power supply				
Charging time:	12 h			
Input voltage:	220 V - 240 V AC 50 Hz			
Mains adapter/adapter included:	EURO			
Operating time (Backlight off):	80 h			
Operating time (Backlight on):	40 h			
Rechargeable battery:	Rchrg. battery optional			
Roonargouble ballery.	(factory)			
Service				
Adjustment at the location of installation	n:961-248			
DAkkS Certificate:	963-128			
DAkkS Certificate: Verification:	963-128 965-228			
Verification:				
Verification: Category	965-228			
Verification: Category Brand:	965-228 KERN			
Verification: Category Brand: Category: Product Group:	965-228 KERN Balances			
Verification: Category Brand: Category: Product Group: Packaging & shipping	965-228 KERN Balances Industiral scale			
Verification: Category Brand: Category: Product Group: Packaging & shipping Delivery:	965-228 KERN Balances Industiral scale 24 h			
Verification: Category Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH):	965-228 KERN Balances Industiral scale 24 h 490 x 790 x 235 mm			
Verification: Category Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight:	965-228 KERN Balances Industiral scale 24 h 490 x 790 x 235 mm 23,700 kg			
Verification: Category Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight:	965-228 KERN Balances Industiral scale 24 h 490 x 790 x 235 mm 23,700 kg 20,800 kg			
Verification: Category Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight:	965-228 KERN Balances Industiral scale 24 h 490 x 790 x 235 mm 23,700 kg			
Verification: Category Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight:	965-228 KERN Balances Industiral scale 24 h 490 x 790 x 235 mm 23,700 kg 20,800 kg			
Verification: Category Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method:	965-228 KERN Balances Industiral scale 24 h 490 x 790 x 235 mm 23,700 kg 20,800 kg			
Verification: Category Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction	965-228 KERN Balances Industiral scale 24 h 490 x 790 x 235 mm 23,700 kg 20,800 kg Parcel service			

KERN & SOHN GmbH · Ziegelei 1 · 72336 Balingen · Germany · Tel. +49–(0)7433 - 99 33-0 · www.kern-sohn.com

# KERN SXS30K-2LM



Stainless steel platform scale with stainless steel IP68 display and EC type approval [M]

Level indicator:	yes
Material weighing plate:	stainless steel
Revolving screw feet:	yes
Wall mount:	yes
Weighing surface (WxD):	500 x 400 mm

## Piktogramme

### STANDARD

GLP	<u>.</u>	-√+ ⊙ 🤊 )	^-	666			
CAL EXT PRINTER	PCS	TOL	MOVE	IP 68	230 V	DMS	1 DAY

#### OPTION

DAkkS +3 days

#### FACTORY

• 6860. •		*		Μ
RS 232	RS 485	BT	ACCU	+3 DAYS