## KERN RIB6K-3HM



High-quality retail scale with large item memory, user-friendly concept of operation and EC type approval [M]



Measuring system	
Adjustment options:	External calibration
Linearity:	1 g   2 g
Readability [d]:	1 g   2 g
Recommended adjusting weight:	5 kg (F2); 1 kg (F2)
Repeatability:	1 g   2 g
Resolution:	3 3.000
Stabilisation time under laboratory conditions:	2 s
Tare range:	6 kg
Warm up time:	10 min   10 min
Weighing capacity [Max]:	3 kg   6 kg
Weighing system:	Strain gauge
Weighing units:	g kg

Display	
Additional Display possible:	yes
Display digit height:	1,800 cm

Technical data about verification	
Minimum load [Min]:	20 g   40 g
Periodic Verification for Italy:	969-112
Verification approval conforming to 2014/31/EU:	yes
Verification by KERN possible:	yes
Verification class:	III
Verification value [e]:	1 g   2 g

Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	-10 °C
Minimum humidity:	0 %

Power supply	
Charging time:	14 h
Input voltage:	100V-240V AC 50/60Hz 0,400 Amax
Mains adapter/adapter included:	CH EURO UK
	0,400 Amax

n/a:	Mains adapter external
Power supply	
Operating time (Backlight off):	80 h
Operating time (Backlight on):	40 h
Rechargeable battery:	Rchrg. battery optional - intern

Adjustment at the location of installation: 961-24	18

DAkkS Certificate:	963-128
Verification:	965-228

Category	
Brand:	KERN
Category:	Balances
Product Group:	Price computing scale

Packaging & shipping	
Delivery:	24 h
Dimensions packaging (WxDxH):	450 x 400 x 210 mm
Gross weight:	5,500 kg
Net weight:	3,800 kg
Shipping method:	Parcel service

Construction	
Casing material:	Plastic
Dimensions housing (WxDxH):	325 x 340 x 115 mm
of stand:	40,500 cm
Level indicator:	yes
Material weighing plate:	stainless steel
Overall dimensions mounted (WxDxH):	325 x 340 x 405 mm
Revolving screw feet:	yes
Weighing surface (WxD):	294 x 225 mm

## KERN RIB6K-3HM



High-quality retail scale with large item memory, user-friendly concept of operation and EC type approval [M]

## Piktogramme STANDARD Lack Ext Memory Unit 230 V DMS 1 DAY OPTION DAKKS ACCU +3 DAYS FACTORY