KERN 572-31



All-rounder e.g. as precision balance in the laboratory or in harsh industrial applications



Measuring system	
Adjustment options:	External calibration
Linearity:	5 mg
Minimum weight (USP):	4 g
Readability [d]:	1 mg
Recommended adjusting weight:	300 g (F1)
Repeatability:	2 mg
Resolution:	300000
Stabilisation time under laboratory conditions:	3 s
Warm up time:	2 h
Weighing capacity [Max]:	300 g
Weighing system:	Strain gauge
Weighing units:	ct dwt g gn kg lb mo oz t tl (Cn) tl (HK) tl (Singap. Malays) tl (Tw) to
Display	
Display digit height:	1,800 cm

\cap		r		1	r	1	0
	u	u	u	u	u	L	Ч

Counting resolution:	300000	
Mininum piece weight at piece counting (Laboratory:	1 mg	
Mininum piece weight at piece counting (Normal):	10 mg	

Functions	
Conversion function:	yes
Counting function:	yes
Percentage determination:	yes
PRE-TARE function:	yes
Suspended weighing:	Loop
Vibration-free weighing (Animal	yes
weighing program):	
Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	10 °C
Doworowonky	
Power supply	401
Charging time:	10 h
Input voltage:	100 V - 240 V
Mains adapter/adapter included:	CH EURO UK US
n/a:	Mains adapter external
Power supply	
Operating time (Backlight off):	30 h
Operating time (Backlight on):	15 h
Rechargeable battery:	Rchrg. battery optional
Service	
DAkkS Certificate:	963-127
Category	
Brand:	KERN
Category:	Balances
Product Group:	Precision balance
Packaging & shipping	
Delivery:	24 h
Dimensions packaging (WxDxH):	400 x 340 x 220 mm
Gross weight:	3,400 kg
Net weight:	2,300 kg
Shipping method:	Parcel service
Construction	
Casing material:	Cast aluminium alloys
Dimensions housing (WxDxH):	180 x 310 x 85 mm
Level indicator:	yes
Material weighing plate:	stainless steel
Overall dimensions mounted	180 x 310 x 130 mm
(WxDxH):	

KERN 572-31



All-rounder e.g. as precision balance in the laboratory or in harsh industrial applications

Weighing space (ÃxH):	157 43
Weighing surface (d):	106
Piktogramme	
STANDARD	
GLP	🔺 % 🞜 ^- 🛒
CAL EXT RS 232 PRINTER PCS	RECIPE PERCENT UNIT MOVE UNDER
<u>ª</u> ≝ ,	
MULTI DMS 1 DAY	
OPTION	

