
KERN **572-37**







Measuring system	
Adjustment options:	External calibration
Linearity:	50 mg
Minimum weight (USP):	40 g
Readability [d]:	10 mg
Recommended adjusting weight:	2 kg (F1)
Repeatability:	20 mg
Resolution:	300000
Stabilisation time under laboratory conditions:	3 s
Warm up time:	2 h
Weighing capacity [Max]:	3 kg
Weighing system:	Strain gauge
Weighing units:	ct dwt g gn kg lb mo oz t tl (Cn) tl (HK) tl (Singap. Malays) tl (Tw) to

1,800 cm
300000
10 mg
100 mg

Display

Functions	
Conversion function:	yes
Counting function:	yes
Percentage determination:	yes
PRE-TARE function:	yes
Suspended weighing:	Loop
Vibration-free weighing (Animal weighing program):	yes
Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	10°C
Power supply	
Charging time:	10 h
Input voltage:	100 V - 240 V
Mains adapter/adapter included:	CH EURO UK US
n/a:	Mains adapter external
Power supply	
Operating time (Backlight off):	30 h
Operating time (Backlight on):	15 h
Rechargeable battery:	Rchrg. battery optional
Service	
DAkkS Certificate:	963-127
Category	
Brand:	KERN
Category:	Balances
Product Group:	Precision balance
Packaging & shipping	
Delivery:	24 h
Dimensions packaging (WxDxH):	400 x 340 x 220 mm
Gross weight:	4,400 kg
Net weight:	2,300 kg
Shipping method:	D I '
	Parcel service
Construction	Parcel service
Casing material:	Cast aluminium alloys 180 x 310 x 85 mm
	Cast aluminium alloys

Material weighing plate:

(WxDxH):

Overall dimensions mounted

stainless steel

180 x 310 x 90 mm

KERN 572-37

ACCU +3 DAYS



All-rounder e.g. as precision balance in the laboratory or in harsh industrial applications

Weighing surface (d):

Piktogramme

STANDARD

STANDARD

CALEXT RS 232 PRINTER PCS RECIPE PERCENT UNIT MOVE UNDER

MULTI DMS 1 DAY

OPTION

DARKS