## KERN CPB30K5DM



Professional model, also with EC type approval [M], counting resolution up to 60,000 points



Measuring system			
Adjustment options:	External calibration		
Linearity:	10 g   20 g		
Readability [d]:	5g 10g		
Recommended adjusting weight:	20 kg (F2); 10 kg (F2)		
Repeatability:	5 g   10 g		
Resolution:	3 3.000		
Stabilisation time under laboratory conditions:	2 s		
Tare range:	29,990 kg		
Warm up time:	10 min   10 min		
Weighing capacity [Max]:	15 kg   30 kg		
Weighing system:	Strain gauge		
Weighing units:	kg		
Display			
Display digit height:	2 cm		
Technical data about verification			
Minimum load [Min]:	100 g		
Periodic Verification for Italy:	969-112		
Verification approval conforming to 2014/31/EU:	yes		
Verification by KERN possible:	yes		
Verification class:	III		
Verification value [e]:	5 g   10 g		
Counting			
Counting resolution:	60000		
Mininum piece weight at piece counting (Laboratory:	500 mg		
Mininum piece weight at piece counting (Normal):	5 g		
Reference weight:	yes		

Functions				
Counting function:	yes			
Function to save totals:	yes			
PRE-TARE function:	yes			
Weighing with tolerance range:	yes			
Environmental conditions				
Maximum humidity:	80 %			
Maximum operating temperature:	40 °C			
Minimum ambient temperature:	-10 °C			
Minimum humidity:	0 %			
Power supply				
Charging time:	12 h			
Input voltage:	100 V - 240 V 50 / 60 Hz			
Mains adapter/adapter included:	CH EURO UK US			
n/a:	Mains adapter external			
Power supply				
Operating time (Backlight off):	90 h			
Operating time (Backlight on):	50 h			
Rechargeable battery:	Rchrg. battery optional - intern			
Service				
	061.249			
Adjustment at the location of installation	511.901-240			
DAkkS Certificate:	963-128			
Verification:	965-228			
Category				
Brand:	KERN			
Category:	Balances			
Product Group:	Counting scale			
Packaging & shipping				
Delivery:	24 h			
Dimensions packaging (WxDxH):	445 x 375 x 220 mm			
Gross weight:	4,310 kg			
Net weight:	3,410 kg			
Shipping method:	Parcel service			
Construction				
Casing material:	Plastic			
Dimensions device (WxDxH):	315 x 350 x 125 mm			
Dimensions housing (WxDxH):	315 x 350 x 110 mm			
Dimensions of display device (WxDxH):	315 x 350 x 130 mm			

KERN & SOHN GmbH · Ziegelei 1 · 72336 Balingen · Germany · Tel. +49–(0)7433 - 99 33-0 · www.kern-sohn.com

## KERN CPB30K5DM

KERN

Professional model, also with EC type approval [M], counting resolution up to 60,000 points

Level indicator:	yes
Material weighing plate:	stainless steel
Overall dimensions mounted (WxDxH):	320 x 350 x 125 mm
Revolving screw feet:	yes
Weighing surface (WxD):	295 x 225 mm

## Piktogramme

## STANDARD

T 0.000	<u>.</u>	<b>H</b>				
CAL EXT RS 232	PCS	SUM	TOL	MULTI	DMS	1 DAY

OPTION



FACTORY

