

Product Specifications

FlashCheck. Waterproof Dishwasher Thermometer Kit

Measurement Range	-40°F to 311°F (-40°C to 155°C)
Operating Range	32°F to 122°F (0°C to 50°C)
Accuracy	±1°F (14°F to 194°F), ±0.5°C (-10°C to 90°C) or ±1% whichever is greatest
Sensor	Thermistor
Display Resolution	0.1°F /°C
Display Reading Update	1 second
Display Window Size	0.77 in W x 0.37 in H (19.5 mm W x 9.5 mm H)
Calibration	Auto calibration feature
Battery	Button Cell Alkaline
Body Casing	ABS plastic
Probe Dimensions	0.14 in. (Dia.) x 4.13 in. (L) (3.56 mm x 105 mm)
Thermometer Weight	1.3 oz (37.6g)
Waterproof Rating	IP65
Certification	Manufacturers certificate of compliance available from DeltaTrak, NIST traceable, NSF, CE



Model 12214

- NSF certified thermometer
- °F/°C selectable
- Min/Max memory stores lowest/highest readings
- Automatic calibration feature
- IP65 waterproof housing
- Waterproof plastic protective heat shield with velcro strap
- Verifies compliance with FDA food code 4-703.11(B), for commercial dishwashers

Importør:
Impex Produkter AS
Gamle Drammensvei 107
1363 Høvik
www.impex.no
info@impex.no
Tel.: 22 32 77 20

DeltaTrak manufactures products under an ISO 9001:2008 registered quality management system

SS0016 15G1

