# KERN IXS 100K-2LM



Platform scale with stainless steel display device with IP68 rating, XL display und EC type approval [M] â now also as high resolution version with high-resolution display



Measuring system	
Adjustment options:	External calibration
Linearity:	20 g   50 g
Load cell connection:	4-Leiter
Number of weighing ranges:	2
Readability [d]:	20 g   50 g
Recommended adjusting weight:	150 kg (M1)
Repeatability:	20 g   50 g
Resolution:	3 3.000
Stabilisation time under laboratory conditions:	2 s
Tare range:	-150 kg
Warm up time:	10 min   10 min
Weighing capacity [Max]:	60 kg   150 kg
Weighing system:	Strain gauge
Weighing units:	kg

Display	
Display digit height:	5.500 cm

Technical data about verification	
Minimum load [Min]:	400 g   1000 g
Periodic Verification for Italy:	969-112
Verification approval conforming to 2014/31/EU:	yes
Verification by KERN possible:	yes
Verification class:	III
Verification value [e]:	20 g   50 g

Counting		
Counting resolution:	30000	
Mininum piece weight at piece counting (Laboratory:	5 g	
Mininum piece weight at piece counting (Normal):	50 g	

Functions		
Counting function:	yes	
Data hold function:	yes	
Help function on the display:	yes	
Peak function:	yes	
PRE-TARE function:	yes	
Vibration-free weighing (Animal weighing program):	yes	
Weighing with tolerance range:	yes	

Environmental conditions		
Maximum humidity:	80 %	
Maximum operating temperature:	40 °C	
Minimum ambient temperature:	-10 °C	
Minimum humidity:	0 %	

Power supply	
Charging time:	12 h
Input voltage:	220 V - 240 V AC 50 Hz
Mains adapter/adapter included:	EURO
Operating time (Backlight off):	80 h
Operating time (Backlight on):	40 h
Rechargeable battery:	Rchrg. battery optional (factory)

Adjustment at the location of in	stallation: 961-249	
DAkkS Certificate:	963-129	
Verification:	965-229	

Service

Category	
Brand:	KERN
Category:	Balances
Product Group:	Industiral scale

Packaging & Snipping	
Delivery:	24 h
Dimensions packaging (WxDxH):	590 x 925 x 245 mm
Gross weight:	38 kg
Net weight:	35 kg
Shipping method:	Parcel service

Counting		Construction		
Counting resolution:	30000	Cable length of display device:	2,500 m	
Mininum piece weight at piece counting (Laboratory:	5 g	Dimensions of display device (WxDxH):	232 x 170 x 80 mm	
Mininum piece weight at piece counting (Normal):	50 g	Dimensions of weighing plate (WxDxH): 49–(0)7433 - 99 33-0 · www.kern-sohn.com	650 x 500 x 133,5 mm	1
VEKIN & SOLIN GUIDH . Ziegelei 1 . 12	330 Dailingen Germany Hei. +	43-(U)1433 - 33 33-U WWW.KEIII-SOIII.COIII		- 1

## KERN IXS 100K-2LM



Platform scale with stainless steel display device with IP68 rating, XL display und EC type approval [M] â now also as high resolution version with high-resolution display

Level indicator: yes

Material weighing plate: stainless steel

Revolving screw feet: yes Wall mount: yes

Weighing surface (WxD): 650 x 500 mm

## Piktogramme

### STANDARD









### **FACTORY**









MOVE

IP65 IP68

230 V