KERN IXS 10K-4L



ves

Platform scale with stainless steel display device with IP68 rating, XL display und EC type approval [M] â now also as high resolution version with high-resolution display



Measuring system	
Adjustment options:	External calibration
Linearity:	1,500 g
Load cell connection:	4-Leiter
Number of weighing ranges:	1
Readability [d]:	500 mg
Recommended adjusting weight:	15 kg (M1)
Repeatability:	500 mg
Resolution:	30000
Stabilisation time under laboratory conditions:	2 s
Tare range:	-15 kg
Warm up time:	2 h
Weighing capacity [Max]:	15 kg
Weighing system:	Strain gauge
Weighing units:	kg
Display	

Counting	
Counting resolution:	30000
Mininum piece weight at piece counting (Laboratory:	500 mg
Mininum piece weight at piece counting (Normal):	5 g

5,500 cm

Display digit height:

Functions		
Counting function:	yes	
Data hold function:	yes	
Help function on the display:	yes	
Peak function:	yes	
PRE-TARE function:	yes	
Vibration-free weighing (Animal	yes	

-	9	9	,				
Francisco de La caracteria de la constante de							
- nvir	onmental condit	เกทร					
	brillioniai conai	.10110					
Envir	onmental condit	tions					

Maximum humidity: 80 %

Maximum operating temperature: 40 °C

Minimum ambient temperature: -10 °C

Minimum humidity: 0 %

Power supply

Weighing with tolerance range:

Charging time: 12 h

Input voltage: 220 V - 240 V AC 50 Hz

Mains adapter/adapter included: EURO
Operating time (Backlight off): 80 h
Operating time (Backlight on): 40 h

Rechargeable battery: Rchrg. battery optional

(factory)

Service

Adjustment at the location of installation: 961-248

DAkkS Certificate: 963-128

Category

Brand: KERN

Category: Balances

Product Group: Industiral scale

Packaging & shipping

Delivery: 24 h
Dimensions packaging (WxDxH): 490 x 630 x 212 mm

Gross weight: 13,800 kg

Net weight: 10,500 kg

Shipping method: Parcel service

Construction

Cable length of display device: 2,500 m

Dimensions of display device 232 x 170 x 80 mm
(WxDxH):

Dimensions of weighing plate 400 x 300 x 89 mm
(WxDxH):

Level indicator: yes

Material weighing plate: stainless steel

Material weighing plate: stainless steel
Revolving screw feet: yes
Wall mount: yes
Weighing surface (WxD): 400 x 300 mm

KERN IXS 10K-4L



Platform scale with stainless steel display device with IP68 rating, XL display und EC type approval [M] â now also as high resolution version with high-resolution display

Piktogramme STANDARD LALEXT PCS SUM TOL MOVE IP65 IP68 230 V DMS OPTION DAkkS +3 DAYS FACTORY RS 232 RS 485 BT ACCU +3 DAYS