## KERN IXS300K-2M



Platform scale with stainless steel display device with IP68 rating, XL display und EC type approval [M] â now also as high resolution version with high-resolution display



Measuring system	
Adjustment options:	External calibration
Linearity:	50 g   100 g
Load cell connection:	6-Leiter
Number of weighing ranges:	2
Readability [d]:	50 g   100 g
Recommended adjusting weight:	300 kg (M1)
Repeatability:	50 g   100 g
Resolution:	3 3.000
Stabilisation time under laboratory conditions:	2 s
Tare range:	-300 kg
Warm up time:	10 min   10 min
Weighing capacity [Max]:	150 kg   300 kg
Weighing system:	Strain gauge
Weighing units:	kg
Display	
Display digit height:	5,500 cm
Technical data about verification	
Minimum load [Min]:	1 kg   2 kg
Periodic Verification for Italy:	969-112
Verification approval conforming to 2014/31/EU:	yes
Verification by KERN possible:	yes
Verification class:	III
Verification value [e]:	50 g   100 g
Counting	
Counting resolution:	30000
Mininum piece weight at piece counting (Laboratory:	10 g
Mininum piece weight at piece	100 g

Functions			
Counting function:	yes		
Data hold function:	yes		
Help function on the display:	yes		
Peak function:	yes		
PRE-TARE function:	yes		
Vibration-free weighing (Animal	yes		
weighing program):			
Weighing with tolerance range:	yes		
Environmental conditions			
Maximum humidity:	80 %		
Maximum operating temperature:	40 °C		
Minimum ambient temperature:	-10 °C		
Minimum humidity:	0 %		
Power supply			
Charging time:	12 h		
Input voltage:	220 V - 240 V AC 50 Hz		
Mains adapter/adapter included:	EURO		
Operating time (Backlight off):	80 h		
Operating time (Backlight on):	40 h		
Rechargeable battery:	Rchrg. battery optional (factory)		
Service			
Service Adjustment at the location of installation	n:961-249		
Adjustment at the location of installation	n: 961-249		
Adjustment at the location of installation DAkkS Certificate:	963-129		
Adjustment at the location of installation			
Adjustment at the location of installation DAkkS Certificate:	963-129		
Adjustment at the location of installation DAkkS Certificate: Verification:	963-129		
Adjustment at the location of installation DAkkS Certificate: Verification: Category	963-129 965-229		
Adjustment at the location of installation DAkkS Certificate: Verification: Category Brand:	963-129 965-229 KERN		
Adjustment at the location of installation DAkkS Certificate: Verification: Category Brand: Category: Product Group:	963-129 965-229 KERN Balances		
Adjustment at the location of installation DAkkS Certificate: Verification: Category Brand: Category: Product Group: Packaging & shipping	963-129 965-229 KERN Balances Industiral scale		
Adjustment at the location of installation DAkkS Certificate: Verification: Category Brand: Category: Product Group: Packaging & shipping Delivery:	963-129 965-229 KERN Balances Industiral scale 24 h		
Adjustment at the location of installation DAkkS Certificate: Verification: Category Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH):	963-129 965-229 KERN Balances Industiral scale		
Adjustment at the location of installation DAkkS Certificate: Verification: Category Brand: Category: Product Group: Packaging & shipping Delivery:	963-129 965-229 KERN Balances Industiral scale 24 h		
Adjustment at the location of installation DAkkS Certificate: Verification: Category Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH):	963-129 965-229 KERN Balances Industiral scale 24 h 595 x 925 x 245 mm		
Adjustment at the location of installation DAkkS Certificate: Verification: Category Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight:	963-129 965-229 KERN Balances Industiral scale 24 h 595 x 925 x 245 mm 38 kg		
Adjustment at the location of installation DAkkS Certificate: Verification: Category Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight:	963-129 965-229 KERN Balances Industiral scale 24 h 595 x 925 x 245 mm 38 kg 35 kg		
Adjustment at the location of installation DAkkS Certificate: Verification: Category Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method:	963-129 965-229 KERN Balances Industiral scale 24 h 595 x 925 x 245 mm 38 kg 35 kg		
Adjustment at the location of installation   DAkkS Certificate:   Verification:   Category   Brand:   Category:   Product Group:   Packaging & shipping   Delivery:   Dimensions packaging (WxDxH):   Gross weight:   Net weight:   Shipping method:   Construction   Cable length of display device:   Dimensions of display device	963-129 965-229 KERN Balances Industiral scale 24 h 595 x 925 x 245 mm 38 kg 35 kg Parcel service		
Adjustment at the location of installation   DAkkS Certificate:   Verification:   Category   Brand:   Category:   Product Group:   Packaging & shipping   Delivery:   Dimensions packaging (WxDxH):   Gross weight:   Net weight:   Shipping method:   Construction   Cable length of display device:	963-129 965-229 KERN Balances Industiral scale 24 h 595 x 925 x 245 mm 38 kg 35 kg Parcel service		

counting (Normal): KERN & SOHN GmbH · Ziegelei 1 · 72336 Balingen · Germany · Tel. +49–(0)7433 - 99 33-0 · www.kern-sohn.com

# KERN IXS300K-2M



Platform scale with stainless steel display device with IP68 rating, XL display und EC type approval [M] â now also as high resolution version with high-resolution display

Level indicator:	yes
Material weighing plate:	stainless steel
Revolving screw feet:	yes
Wall mount:	yes
Weighing surface (WxD):	650 x 500 mm

### Piktogramme

### STANDARD

	<i>.</i>			M	444	444	-8=	
CAL EXT	PCS	SUM	TOL	MOVE	IP 65	IP 68	230 V	DMS
1 DAY								

OPTION

DAkks +3 Days

#### FACTORY

			*	E C	Μ
ſ	RS 232	RS 485	BT	ACCU	+3 DAYS