# KERN IXS60K-2LM



Platform scale with stainless steel display device with IP68 rating, XL display und EC type approval [M] â now also as high resolution version with high-resolution display



Measuring system	
Adjustment options:	External calibration
Linearity:	10 g   20 g
Load cell connection:	6-Leiter
Number of weighing ranges:	2
Readability [d]:	10 g   20 g
Recommended adjusting weight:	60 kg (M1)
Repeatability:	10 g   20 g
Resolution:	3 3.000
Stabilisation time under laboratory conditions:	2 s
Tare range:	-60 kg
Warm up time:	10 min   10 min
Weighing capacity [Max]:	30 kg   60 kg
Weighing system:	Strain gauge
Weighing units:	kg

Display	
Display digit height:	5,500 cm

Technical data about verification	
Minimum load [Min]:	200 g   400 g
Periodic Verification for Italy:	969-112
Verification approval conforming to 2014/31/EU:	yes
Verification by KERN possible:	yes
Verification class:	III
Verification value [e]:	10 g   20 g

Counting		
Counting resolution:	30000	
Mininum piece weight at piece counting (Laboratory:	2 g	
Mininum piece weight at piece counting (Normal):	20 g	

Functions		
Counting function:	yes	
Data hold function:	yes	
Help function on the display:	yes	
Peak function:	yes	
PRE-TARE function:	yes	
Vibration-free weighing (Animal weighing program):	yes	
Weighing with tolerance range:	yes	

Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	-10 °C
Minimum humidity:	0 %

Power supply	
Charging time:	12 h
Input voltage:	220 V - 240 V AC 50 Hz
Mains adapter/adapter included:	EURO
Operating time (Backlight off):	80 h
Operating time (Backlight on):	40 h
Rechargeable battery:	Rchrg. battery optional (factory)

Adjustment at the location of ins	stallation: 961-249	
DAkkS Certificate:	963-129	
Verification:	965-229	

Service

Category	
Brand:	KERN
Category:	Balances
Product Group:	Industiral scale

Packaging & snipping	
Delivery:	24 h
Dimensions packaging (WxDxH):	500 x 765 x 230 mm
Gross weight:	23,800 kg
Net weight:	20,500 kg
Shipping method:	Parcel service

Counting		Construction		
Counting resolution:	30000	Cable length of display device:	2,500 m	
Mininum piece weight at piece counting (Laboratory:	2 g	Dimensions of display device (WxDxH):	232 x 170 x 80 mm	
Mininum piece weight at piece counting (Normal): KERN & SOHN GmbH · Ziegelei 1 · 7	20 g 2336 Balingen · Germany · Tel +	Dimensions of weighing plate (WxDxH): 49–(0)7433 - 99 33-0 : www.kern-sohn.com	500 x 400 x 123 mm	1
counting (Laboratory: Mininum piece weight at piece	20 g	(WxDxH):		

## KERN IXS60K-2LM



Platform scale with stainless steel display device with IP68 rating, XL display und EC type approval [M] â now also as high resolution version with high-resolution display

Level indicator: yes

Material weighing plate: stainless steel

Revolving screw feet: yes Wall mount: yes

Weighing surface (WxD): 500 x 400 mm

### Piktogramme

#### STANDARD













#### **OPTION**



#### **FACTORY**









