KERN IXS60K-2M



Platform scale with stainless steel display device with IP68 rating, XL display und EC type approval [M] â now also as high resolution version with high-resolution display



Measuring system	
Adjustment options:	External calibration
Linearity:	10 g 20 g
Load cell connection:	4-Leiter
Number of weighing ranges:	2
Readability [d]:	10 g 20 g
Recommended adjusting weight:	60 kg (M1)
Repeatability:	10 g 20 g
Resolution:	3 3.000
Stabilisation time under laboratory conditions:	2s
Tare range:	-60 kg
Warm up time:	10 min 10 min
Weighing capacity [Max]:	30 kg 60 kg
Weighing system:	Strain gauge
Weighing units:	kg
Display	
Display digit height:	5,500 cm
Technical data about verification	
Minimum load [Min]:	200 g 400 g
Periodic Verification for Italy:	969-112
Verification approval conforming to 2014/31/EU:	yes
Verification by KERN possible:	yes
Verification class:	III
Verification value [e]:	10 g 20 g
Counting	
Counting resolution:	30000
Mininum piece weight at piece counting (Laboratory:	2 g
Mininum piece weight at piece	20 g

Functions				
Counting function:	yes			
Data hold function:	yes			
Help function on the display:	yes			
Peak function:	yes			
PRE-TARE function:	yes			
Vibration-free weighing (Animal	yes			
weighing program):				
Weighing with tolerance range:	yes			
Environmental conditions				
Maximum humidity:	80 %			
Maximum operating temperature:	40 °C			
Minimum ambient temperature:	-10 °C			
Minimum humidity:	0 %			
Power cupply				
Power supply	101			
Charging time:	12 h			
Input voltage:	220 V - 240 V AC 50 Hz			
Mains adapter/adapter included:	EURO			
Operating time (Backlight off):	80 h			
Operating time (Backlight on):	40 h			
Rechargeable battery:	Rchrg. battery optional (factory)			
Service				
Adjustment at the location of installation	:961-249			
DAkkS Certificate:	963-129			
Verification:	965-229			
Category				
Brand:	KERN			
Category:	Balances			
Product Group:	Industiral scale			
Packaging & shipping				
Delivery:	24 h			
Dimensions packaging (WxDxH):	500 x 635 x 222 mm			
Gross weight:	13,050 kg			
Net weight:	10,500 kg			
Shipping method:	Parcel service			
Construction				
Construction	0.500			
Cable length of display device:	2,500 m			
Dimensions of display device (WxDxH):	232 x 170 x 80 mm			
Dimensions of weighing plate	400 x 300 x 89 mm			
(WxDxH):				

1

counting (Normal): KERN & SOHN GmbH · Ziegelei 1 · 72336 Balingen · Germany · Tel. +49–(0)7433 - 99 33-0 · www.kern-sohn.com

KERN IXS60K-2M



Platform scale with stainless steel display device with IP68 rating, XL display und EC type approval [M] â now also as high resolution version with high-resolution display

Level indicator:	yes	
Material weighing plate:	stainless steel	
Revolving screw feet:	yes	
Wall mount:	yes	
Weighing surface (WxD):	400 x 300 mm	

Piktogramme

STANDARD

	<u>.</u>			M	444	444	-6=	
CAL EXT	PCS	SUM	TOL	MOVE	IP 65	IP 68	230 V	DMS
1 DAY								

OPTION

DAkks +3 Days

FACTORY

0.000		*)	Μ	
RS 232	RS 485	BT	ACCU	+3 DAYS	