KERN IXS6K-3M



Platform scale with stainless steel display device with IP68 rating, XL display und EC type approval [M] â now also as high resolution version with high-resolution display



Measuring system	
Adjustment options:	External calibration
Linearity:	1 g 2 g
Load cell connection:	4-Leiter
Number of weighing ranges:	2
Readability [d]:	1 g 2 g
Recommended adjusting weight:	6 kg (M1)
Repeatability:	1 g 2 g
Resolution:	3 3.000
Stabilisation time under laboratory conditions:	2 s
Tare range:	-6 kg
Warm up time:	10 min 10 min
Weighing capacity [Max]:	3 kg 6 kg
Weighing system:	Strain gauge

Display	
Display digit height:	5,500 cm

Technical data about verification	
Minimum load [Min]:	20 g 40 g
Periodic Verification for Italy:	969-112
Verification approval conforming to 2014/31/EU:	yes
Verification by KERN possible:	yes
Verification class:	III
Verification value [e]:	1 g 2 g

Counting		
Counting resolution:	30000	
Mininum piece weight at piece counting (Laboratory:	200 mg	
Mininum piece weight at piece counting (Normal):	2 g	

Functions	
Counting function:	yes
Data hold function:	yes
Help function on the display:	yes
Peak function:	yes
PRE-TARE function:	yes
Vibration-free weighing (Animal weighing program):	yes
Weighing with tolerance range:	yes
Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	40 °C

Power supply	
Charging time:	12 h
Input voltage:	220 V - 240 V AC 50 Hz
Mains adapter/adapter included:	EURO
Operating time (Backlight off):	80 h
Operating time (Backlight on):	40 h
Rechargeable battery:	Rchrg. battery optional (factory)

Minimum ambient temperature:

Minimum humidity:

-10 °C

0 %

Service		
Adjustment at the location of ins	tallation: 961-248	
DAkkS Certificate:	963-128	
Verification:	965-228	

Category	
Brand:	KERN
Category:	Balances
Product Group:	Industiral scale

Packaging & shipping	
Delivery:	24 h
Dimensions packaging (WxDxH):	490 x 570 x 212 mm
Gross weight:	7 kg
Net weight:	5,100 kg
Shipping method:	Parcel service

Construction	
Cable length of display device:	2,500 m
Dimensions of display device (WxDxH):	232 x 170 x 80 mm
Dimensions of weighing plate (WxDxH):	300 x 240 x 86 mm

KERN IXS6K-3M



Platform scale with stainless steel display device with IP68 rating, XL display und EC type approval [M] â now also as high resolution version with high-resolution display

Level indicator: yes

Material weighing plate: stainless steel

Revolving screw feet: yes

Wall mount: yes

Weighing surface (WxD): 300 x 240 mm

Piktogramme

STANDARD



1 DAY

OPTION



FACTORY

