KERN FOB30K-3NL



Stainless steel bench scale with large weighing range and IP67 protection against dust and water splashes



Measuring system	
Adjustment options:	External calibration
Linearity:	6 g 15 g
Readability [d]:	2g 5g
Recommended adjusting weight:	20 kg (M1)
Repeatability:	2g 5g
Resolution:	8 6.000
Stabilisation time under laboratory conditions:	2 s
Warm up time:	30 min 30 min
Weighing capacity [Max]:	16 kg 30 kg
Weighing system:	Strain gauge
Weighing units:	g lb oz

Display	
Display digit height:	2,500 cm

Environmental conditions	
Maximum humidity:	95 %
Maximum operating temperature:	35 °C
Minimum ambient temperature:	5°C
Minimum humidity:	25 %

Power supply	
Battery:	4x1.5 V AA
Input voltage:	230 V AC 50 Hz

n/a:	Mains adapter external

Power supply

Operating time: 48 h

Service

Adjustment at the location of installation: 961-248

DAkkS Certificate: 963-128

Category	
Brand:	KERN
Category:	Balances
Product Group:	Bench scale

Pac	kaninc	1 L C	hinni	na
1 ac	kaging	y ca s	ιπρρι	II IY

Delivery:	24 h
Dimensions packaging (WxDxH):	415 x 305 x 165 mm
Gross weight:	4,550 kg
Net weight:	3,750 kg
Shipping method:	Parcel service

Construction	
Casing material:	stainless steel
Dimensions housing (WxDxH):	285 x 255 x 90 mm
Dimensions of weighing plate (WxDxH):	252 x 200 x 14 mm
Material weighing plate:	stainless steel
Weighing surface (WxD):	252 x 200 mm

Piktogramme

STANDARD



OPTION

