# KERN BFA6T-3M



Weighing bridge with screw-on weighing plate (IP67) and stainless steel display device (IP65), with EC type approval [M]



Measuring system			
Adjustment options:	External calibration		
Linearity:	2 kg		
Load cell connection:	6-Leiter		
Readability [d]:	2 kg		
Recommended adjusting weight:	6000 kg (M2)		
Repeatability:	2 kg		
Resolution:	3000		
Stabilisation time under laboratory conditions:	2 s		
Tare range:	-6 t		
Warm up time:	10 min		
Weighing capacity [Max]:	6 t		
Weighing system:	Strain gauge		
Weighing units:	kg		

Display

Display digit height:

### Technical data about verification

Minimum load [Min]:	40 kg
Periodic Verification for Italy:	969-112
Verification approval conforming to 2014/31/EU:	yes
Verification by KERN possible:	yes
Verification class:	III
Verification value [e]:	2 kg

5,200 cm

#### Functions

Counting function:	yes
Function to save totals:	yes
Vibration-free weighing (Animal weighing program):	yes

Environmental conditions				
Maximum humidity:	80 %			
Maximum operating temperature:	40 °C			
Minimum ambient temperature:	-10 °C			
Minimum humidity:	0 %			
Development				
Power supply				
Charging time:	12 h			
Input voltage:	100 V - 240 V 50 / 60 Hz			
Mains adapter:	Mains adapter external			
Mains adapter/adapter included:	CH EURO UK US			
Operating time (Backlight off):	50 h			
Operating time (Backlight on):	20 h			
Service				
Adjustment at the location of installation	:961-252			
DAkkS Certificate:	963-132			
Verification:	965-232			
Category				
Brand:	KERN			
Category:	Balances Floor scale			
Product Group:	FIOUI Scale			
Packaging & shipping				
Delivery:	120 h			
Dimensions packaging (WxDxH):	1550 x 1550 x 350 mm			
Gross weight:	220 kg			
Net weight:	210 kg			
Shipping method:	Freight forwarder			
UN number:	2800			
Construction				
Cable length of display device:	5 m			
Dimensions housing (WxDxH):	266 x 165 x 96 mm			
Dimensions of display device	266 x 165 x 96 mm			
(WxDxH):				
Dimensions of weighing plate	1500 x 1500 x 130 mm			
(WxDxH):				
Level indicator:	yes			
Revolving screw feet:	yes			
Wall mount:	yes			
Weighing surface (WxD):	1500 x 1500 mm			

Weighing with tolerance range: yes KERN & SOHN GmbH · Ziegelei 1 · 72336 Balingen · Germany · Tel. +49–(0)7433 - 99 33-0 · www.kern-sohn.com

## KERN BFA6T-3M



Weighing bridge with screw-on weighing plate (IP67) and stainless steel display device (IP65), with EC type approval [M]

### Piktogramme

#### STANDARD

CAL EXT	<u>.</u>	<b>A</b>		M	444	444	B	
CAL EXT	PCS	SUM	TOL	MOVE	IP 65	IP 67	MULTI	DMS
E D								

2 DAYS

OPTION

DAkks +3 days

FACTORY

