

TA 888

Hot wire anemometer with temperature indication



Application profile

Ideal for HVAC measurements. Robust instrument with a lot of useable features.

Product features

- Large display to indicate two measurements simultaneously
- MAX-MIN-function
- Average measurement for 20 values
- 0.01 m/s display resolution
- Easy to use Volume Flow measurement
- Backlight
- Disable Auto-OFF-function
- Incl. Windows Software for Online Documentation
- Incl. 230 VAC Powerpack
- Cable length 1.8 m

Technical data

Air velocity:

Measuring range:	0.10 ... 15 m/s
Resolution:	0.01 m/s
Accuracy:	±5% FS

Temperature:

Measuring range:	0 ... +50°C
Resolution:	0,1°C / 0.1°C
Accuracy:	±2%

Display:	7 segment LCD (2-line)
-----------------	------------------------

Power supply:	1x 9V battery
----------------------	---------------

Housing:	plastic (ABS)
-----------------	---------------

210 x 75 x 50 mm (L x B/W x H)

Dimensions:

Weight:	2,050 g
----------------	---------

m/s
0°C...+50°C
MAX-MIN
AVG
BACKLIGHT
USB

Areas of application

- Measuring air velocity in ducts
- Volume flow measurements at air condition systems
- Checking air filter system
- Measuring the environment conditions at working places
- Measurements of the energy branch