## KERN BFB600K-1NM



Weighing bridge with screw-on weighing plate (IP67) and XXL display device, with EC type approval [M]



| Measuring system                                |                      |  |
|---|----------------------|--|
| Adjustment options:                             | External calibration |  |
| Linearity:                                      | 400 g                |  |
| Load cell connection:                           | 4-Leiter             |  |
| Readability [d]:                                | 200 g                |  |
| Recommended adjusting weight:                   | 600 kg (M2)          |  |
| Repeatability:                                  | 200 g                |  |
| Resolution:                                     | 3000                 |  |
| Stabilisation time under laboratory conditions: | 2 s                  |  |
| Tare range:                                     | -600 kg              |  |
| Warm up time:                                   | 10 min               |  |
| Weighing capacity [Max]:                        | 600 kg               |  |
| Weighing system:                                | Strain gauge         |  |
| Weighing units:                                 | kg                   |  |
| Display   |                      |  |

Technical data about verification

Display digit height:

| Minimum load [Min]:                             | 4 kg    |
|---|---------|
| Periodic Verification for Italy:                | 969-112 |
| Verification approval conforming to 2014/31/EU: | yes     |
| Verification by KERN possible:                  | yes     |
| Verification class:                             | III     |
| Verification value [e]:                         | 200 g   |

5,200 cm

## Functions

| Counting function:              | yes |
|---------------------------------|-----|
| Function to save totals:        | yes |
| Vibration-free weighing (Animal | yes |
| weighing program):              |     |
|                                 |     |

| Environmental conditions                   |                                   |  |  |
|--|-----------------------------------|--|--|
| Maximum humidity:                          | 80 %                              |  |  |
| Maximum operating temperature:             | 40 °C                             |  |  |
| Minimum ambient temperature:               | -10 °C                            |  |  |
| Power supply                               |                                   |  |  |
|  | 40.5                              |  |  |
| Charging time:                             | 10 h                              |  |  |
| Input voltage:                             | 100 V - 240 V 50 / 60 Hz          |  |  |
| Mains adapter:                             | Mains adapter external            |  |  |
| Mains adapter/adapter included:            | CH EURO UK US                     |  |  |
| Operating time (Backlight off):            | 35 h                              |  |  |
| Operating time (Backlight on):             | 8 h                               |  |  |
| Rechargeable battery:                      | Rchrg. battery optional (factory) |  |  |
| Service                                    |                                   |  |  |
| Adjustment at the location of installation | on: 961-250                       |  |  |
| DAkkS Certificate:                         | 963-130                           |  |  |
| Verification:                              | 965-230                           |  |  |
| Category                                   |                                   |  |  |
| Brand:                                     | KERN                              |  |  |
| Category:                                  | Balances                          |  |  |
| Product Group:                             | Floor scale                       |  |  |
| Packaging & shipping                       |                                   |  |  |
| Delivery:                                  | 48 h                              |  |  |
| Dimensions packaging (WxDxH):              | 1610 x 1320 x 330 mm              |  |  |
| Gross weight:                              | 195 kg                            |  |  |
| Net weight:                                | 135 kg                            |  |  |
| Shipping method:                           | Freight forwarder                 |  |  |
| Construction                               |                                   |  |  |
| Cable length of display device:            | 5 m                               |  |  |
| Dimensions of display device<br>(WxDxH):   | 250 x 160 x 58 mm                 |  |  |
| Dimensions of weighing plate<br>(WxDxH):   | 1500 x 1250 x 85 mm               |  |  |
| Level indicator:                           | yes                               |  |  |
| Revolving screw feet:                      | yes                               |  |  |
| Wall mount:                                | yes                               |  |  |
| Weighing surface (WxD):                    | 1500 x 1250 mm                    |  |  |

Weighing with tolerance range: yes KERN & SOHN GmbH · Ziegelei 1 · 72336 Balingen · Germany · Tel. +49–(0)7433 - 99 33-0 · www.kern-sohn.com

## KERN BFB600K-1NM



Weighing bridge with screw-on weighing plate (IP67) and XXL display device, with EC type approval [M]

| Piktogramme | )            |  |
|-------------|--------------|--|
| STANDARD    |              |  |
| CAL EXT     |              |  |
| DMS         |              |  |
| OPTIC       |              |  |
| DAkkS       |              |  |
| +3 DAYS     |              |  |
|             | NALOG        |  |
| BT 2.0      | ACCU +3 DAYS |  |