KERN BID1T-4DSM



Floor scale with EC type approval [M] and the best price-performance ratio - now also as a high-resolution dual-range balance



Measuring system			
Adjustment options:	External calibration		
Linearisation (points):	3		
Linearity:	600 g 1500 g		
Load cell connection:	4-Leiter		
Readability [d]:	200 g 500 g		
Recommended adjusting weight:	1500 kg (M1)		
Repeatability:	200 g 500 g		
Resolution:	3 3.000		
Stabilisation time under laboratory conditions:	2 s		
Tare range:	-1,500 t		
Warm up time:	10 min 10 min		
Weighing capacity [Max]:	600 kg 1500 kg		
Weighing system:	Strain gauge		
Weighing units:	g HJ kg lb oz PCS tJ		
Display			
Display digit height:	2,500 cm		
Display digit height:	2,500 cm		
Technical data about verification			

Minimum load [Min]:	4 kg 10 kg
Periodic Verification for Italy:	969-112
Verification approval conforming to 2014/31/EU:	yes
Verification by KERN possible:	yes
Verification class:	III
Verification value [e]:	200 g 500 g

Functions			
Counting function:	yes		
Percentage determination:	yes		
PRE-TARE function:	yes		
Vibration-free weighing (Animal weighing program):	yes		
Weighing with tolerance range:	yes		
Environmental conditions			
Maximum humidity:	80 %		
Minimum humidity:	0 %		
Power supply			
Charging time:	3 h		
Input voltage:	100V-240V AC 50/60Hz 0,400 Amax		
Mains adapter/adapter included:	EURO UK US		
Operating time:	100 h		
Operating time (Backlight off):	43 h		
Operating time (Backlight on):	26 h		
Rechargeable battery:	Rchrg. battery optional - intern		
Service			
Adjustment at the location of installation	on:961-250		
DAkkS Certificate:	963-130		
Verification:	965-230		
Category			
Brand:	KERN		
Category:	Balances		
Product Group:	Floor scale		
Packaging & shipping			
Delivery:	48 h		
Dimensions packaging (WxDxH):	1050 x 1050 x 260 mm		
Gross weight:	95 kg		
Net weight:	67 kg		
Shipping method:	Freight forwarder		
Construction			
Cable length:	5 m		
Cable length of display device:	5 m		
Dimensions of display device (WxDxH):	268 x 115 x 80 mm		
Dimensions of weighing plate (WxDxH):	1000 x 1000 x 108 mm		

KERN BID1T-4DSM



Floor scale with EC type approval [M] and the best price-performance ratio - now also as a high-resolution dual-range balance

Level indicator:	yes
Revolving screw feet:	yes
Wall mount:	yes
Weighing surface (WxD):	1000 x 1000 mm

Piktogramme

STANDARD

CAL EXT		KCP PROTOCOL			the second se	% Percent	-√+ ⊙ Э) TOL	MOVE
444	444							
IP 65	IP 67	MULTI	DMS	2 DAYS				

FACTORY

•	*	().		Μ	
USB	BT 4.0	WLAN	LAN	+3 DAYS	