


KERN BID600K-1DSM



Floor scale with EC type approval [M] and the best price-performance ratio - now also as a high-resolution dual-range balance



Measuring system

| | |
|---|----------------------|
| Adjustment options: | External calibration |
| Linearisation (points): | 3 |
| Linearity: | 300 g 600 g |
| Load cell connection: | 4-Leiter |
| Readability [d]: | 100 g 200 g |
| Recommended adjusting weight: | 600 kg (M1) |
| Repeatability: | 100 g 200 g |
| Resolution: | 3 3.000 |
| Stabilisation time under laboratory conditions: | 2 s |
| Tare range: | -600 kg |
| Warm up time: | 10 min 10 min |
| Weighing capacity [Max]: | 300 kg 600 kg |
| Weighing system: | Strain gauge |
| Weighing units: | g HJ kg lb oz PCS tJ |

Display

| | |
|-----------------------|----------|
| Display digit height: | 2,500 cm |
| Display digit height: | 2,500 cm |

Technical data about verification

| | |
|---|---------------|
| Minimum load [Min]: | 2 kg 4 kg |
| Periodic Verification for Italy: | 969-112 |
| Verification approval conforming to 2014/31/EU: | yes |
| Verification by KERN possible: | yes |
| Verification class: | III |
| Verification value [e]: | 100 g 200 g |

Functions

| | |
|--|-----|
| Counting function: | yes |
| Percentage determination: | yes |
| PRE-TARE function: | yes |
| Vibration-free weighing (Animal weighing program): | yes |
| Weighing with tolerance range: | yes |

Environmental conditions

| | |
|-------------------|------|
| Maximum humidity: | 80 % |
| Minimum humidity: | 0 % |

Power supply

| | |
|---------------------------------|------------------------------------|
| Charging time: | 3 h |
| Input voltage: | 100V-240V AC 50/60Hz 0,400 Amax |
| Mains adapter/adaptor included: | EURO UK US |
| Operating time: | 100 h |
| Operating time (Backlight off): | 43 h |
| Operating time (Backlight on): | 26 h |
| Rechargeable battery: | Rchrg. battery optional - intern |

Service

| | |
|---|---------|
| Adjustment at the location of installation: | 961-250 |
| DAkkS Certificate: | 963-130 |
| Verification: | 965-230 |

Category

| | |
|----------------|-------------|
| Brand: | KERN |
| Category: | Balances |
| Product Group: | Floor scale |

Packaging & shipping

| | |
|-------------------------------|----------------------|
| Delivery: | 48 h |
| Dimensions packaging (WxDxH): | 1110 x 1035 x 130 mm |
| Gross weight: | 95 kg |
| Net weight: | 67 kg |
| Shipping method: | Freight forwarder |

Construction

| | |
|---------------------------------------|----------------------|
| Cable length: | 5 m |
| Cable length of display device: | 5 m |
| Dimensions of display device (WxDxH): | 268 x 115 x 80 mm |
| Dimensions of weighing plate (WxDxH): | 1000 x 1000 x 108 mm |

KERN BID600K-1DSM



Floor scale with EC type approval [M] and the best price-performance ratio - now also as a high-resolution dual-range balance

| | |
|-------------------------|----------------|
| Level indicator: | yes |
| Revolving screw feet: | yes |
| Wall mount: | yes |
| Weighing surface (WxD): | 1000 x 1000 mm |

Piktogramme

STANDARD



FACTORY

