KERN SFB60K-2XLM



Stainless steel platform scales with IP65 protection, also with XL platform or EC type approval [M]



Measuring system	
Adjustment options:	External calibration
Linearity:	20 g
Load cell connection:	6-wire
Readability [d]:	20 g
Recommended adjusting weight:	60 kg (M1)
Repeatability:	20 g
Resolution:	3000
Stabilisation time under laboratory conditions:	2 s
Tare range:	-60 kg
Warm up time:	10 min
Weighing capacity [Max]:	60 kg
Weighing system:	Strain gauge
Weighing units:	kg

Display digit height:	5,200 cm
Technical data about verification	
Minimum load [Min]:	400 a

Display

lecillical data about verification	
Minimum load [Min]:	400 g
Periodic Verification for Italy:	969-112
Verification approval conforming to 2014/31/EU:	yes
Verification by KERN possible:	yes
Verification class:	III
Verification value [e]:	20 g

Functions		
Counting function:	yes	
Function to save totals:	yes	
Vibration-free weighing (Animal weighing program):	yes	
Weighing with tolerance range:	ves	

Environmental conditions	
Maximum humidity:	95 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	-10 °C
Minimum humidity:	0 %

Power supply	
Charging time:	12 h
Input voltage:	110 V - 230 V AC
Mains adapter:	Mains adapter external
Mains adapter/adapter included:	CH EURO UK US
Operating time (Backlight off):	35 h
Operating time (Backlight on):	20 h

Service		
Adjustment at the location of ins	tallation: 961-249	
DAkkS Certificate:	963-129	
Verification:	965-229	

Category	
Brand:	KERN
Category:	Balances
Product Group:	Industiral scale

24 h
555 x 940 x 220 mm
18,040 kg
15,260 kg
Parcel service
2800

Construction	
Cable length of display device:	3 m
Dimensions of display device (WxDxH):	266 x 165 x 96 mm
Dimensions of weighing plate (WxDxH):	500 x 400 x 137 mm
Level indicator:	yes
Material weighing plate:	stainless steel
Overall dimensions mounted (WxDxH):	500 x 560 x 590 mm
Revolving screw feet:	yes
Wall mount:	yes
Weighing surface (WxD):	500 x 400 mm

KERN SFB60K-2XLM



Stainless steel platform scales with IP65 protection, also with XL platform or EC type approval [M]

Piktogramme STANDARD KCP GLP SUM TOL IP 65 IP 67 ACCU B I DMS 1 DAY OPTION DAKKS +3 DAYS

FACTORY

RS 232 +3 DAYS