KERN IOC 300K-2M

All-round platform scale with a range of communication options and EC type approval [M]





Measuring system	
Adjustment options:	External calibration
Linearisation (points):	3
Linearity:	150 g 300 g
Load cell connection:	6-Leiter
Readability [d]:	50 g 100 g
Recommended adjusting weight:	300 kg (M1)
Repeatability:	50 g 100 g
Resolution:	3 3.000
Stabilisation time under laboratory conditions:	2 s
Tare range:	-300 kg
Warm up time:	10 min 10 min
Weighing capacity [Max]:	150 kg 300 kg
Weighing system:	Strain gauge
Weighing units:	g HJ kg lb oz PCS tJ

Display		
Display digit height:	2,500 cm	
Display digit height:	2,500 cm	

Technical data about verification		
Minimum load [Min]:	1 kg 2 kg	
Periodic Verification for Italy:	969-112	
Verification approval conforming to 2014/31/EU:	yes	
Verification by KERN possible:	yes	
Verification class:	III	
Verification value [e]:	50 g 100 g	

Counting		
Counting resolution:	30000	
Mininum piece weight at piece counting (Laboratory:	10 g	
Mininum piece weight at piece counting (Normal):	100 g	

Functions	
Counting function:	yes
Percentage determination:	yes
PRE-TARE function:	yes
Vibration-free weighing (Animal weighing program):	yes
Weighing with tolerance range:	yes
Environmental conditions	
Maximum humidity:	80 %
	40.00

Maximum mannanty.	00 70
Maximum operating temperature:	40 °C
Minimum ambient temperature:	-10 °C
Minimum humidity:	0 %
Power supply	
Charging time:	3 h
Input voltage:	100V-240V AC 50/60Hz

Input voltage:	100V-240V AC 50/60Hz 0,400 Amax
Mains adapter:	Mains adapter external
Mains adapter/adapter included:	EURO UK US
Operating time:	100 h
Operating time (Backlight off):	43 h
Operating time (Backlight on):	26 h
Rechargeable battery:	Rchrg. battery optional -

-	·	intern	
Service			

Adjustment at the location of installation: 961-249

DAkkS Certificate: 963-129 Verification: 965-229

Category	
Brand:	KERN
Category:	Balances
Product Group:	Industiral scale

Packaging & shipping	
Delivery:	24 h
Dimensions packaging (WxDxH):	1050 x 740 x 175 mm
Gross weight:	24,720 kg
Net weight:	21,900 kg
Shipping method:	Parcel service

Construction	
Cable length of display device:	3 m
Dimensions of display device (WxDxH):	268 x 115 x 80 mm
Dimensions of weighing plate (WxDxH):	650 x 500 x 150 mm

KERN IOC300K-2M



All-round platform scale with a range of communication options and EC type approval [M]

Level indicator:	yes
Material weighing plate:	stainless steel
Revolving screw feet:	yes
Wall mount:	yes
Weighing surface (WxD):	650 x 500 mm

Piktogramme

STANDARD



OPTION



FACTORY

