KERN ALS 160-4A



Analytical balance range with large weighing ranges - now also with EC type approval [M] or available as semi-micro analytical balance



Measuring system	
Adjustment options:	External calibration
Linearity:	0,300 mg
Minimum weight (USP):	200 mg
Readability [d]:	0,100 mg
Recommended adjusting weight:	150 g (E2)
Repeatability:	0,100 mg
Resolution:	1.600.000
Stabilisation time under laboratory conditions:	4 s
Tare range:	160 g
Warm up time:	8 h
Weighing capacity [Max]:	160 g
Weighing system:	Force compensation
Weighing units:	tl (Tw) gn ozt tl (HK) g mo lb tl (Singap. Malays) ct dwt oz

Display digit height:	1,700 cm
Technical data about verification	
Verification class:	I (ohne Bauartzulassung)

Display

e approvar [ivi]	
Counting	
Counting resolution:	160000
Mininum piece weight at piece counting (Laboratory:	1 mg
Mininum piece weight at piece counting (Normal):	10 mg
Reference weight:	yes
Functions	
Counting function:	yes
Density determination function:	yes
Peak function:	yes
Percentage determination:	yes
PRE-TARE function:	yes
Standby function:	yes
Vibration-free weighing (Animal weighing program):	yes
Weighing with tolerance range:	yes
Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	35 °C
Minimum ambient temperature:	5°C
Power supply	
Input voltage:	country-dependent
Mains adapter:	Mains adapter external
Mains adapter/adapter included:	UK US EURO CH
Service	
DAkkS Certificate:	963-101
Category	
Brand:	KERN
Category:	Balances
Product Group:	Analytical balance
Packaging & shipping	

24 h

9 kg

6,200 kg

Parcel service

520 x 410 x 620 mm

Delivery:

Gross weight:

Shipping method:

Net weight:

Dimensions packaging (WxDxH):

KERN ALS 160-4A



Analytical balance range with large weighing ranges - now also with EC type approval [M] or available as semi-micro analytical balance

Construction	
Casing material:	Plastic
Dimensions draft shield (WxDxH):	180 x 170 x 225 mm
Dimensions housing (WxDxH):	210 x 340 x 330 mm
Level indicator:	yes
Material weighing plate:	stainless steel
Overall dimensions mounted (WxDxH):	210 x 340 x 330 mm
Revolving screw feet:	yes
Weighing space (WxDxH):	160 x 140 x 205 mm
Weighing surface (d):	80

Piktogramme

STANDARD



OPTION



FACTORY

