KERN DAB 200-2



Moisture analyser which is particularly easy to use - now also as a version with [d] = 10 mg, ideal for recurring rapid tests



Measuring system	
Adjustment options:	External calibration
Linearity:	30 mg
Load cell connection:	4-wire
Measuring capacity [Max]:	199 °C
Minimum weight (USP):	20 g
Readability (moisture):	0,050 %
Readability [d]:	10 mg
Repeatability:	10 mg
Resolution:	20000
Stabilisation time under laboratory conditions:	3 s
Tare range:	200 g
Warm up time:	30 min
Weighing capacity [Max]:	200 g
Weighing system:	Strain gauge
Weighing units:	% Trockenmasse g % Feuchte

Display	
Display digit height:	1,400 cm
Display digit height:	6 mm

Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	5°C
Minimum humidity:	5 %

Power supply

Battery: no battery 230 V AC 50 Hz Input voltage:

Mains adapter/adapter included: **EURO**

Service

Adjustment at the location of installation: 961-247

DAkkS Certificate: 963-127 Factory calibration certificate 964-305 (temperature):

Category

Brand: **KERN**

Product Group: Moisture analyser

Packaging & shipping

24 h Delivery:

Dimensions packaging (WxDxH): 490 x 350 x 360 mm

Gross weight: 6,100 kg Net weight: 4,820 kg Shipping method: Parcel service

Construction

Level indicator: yes Aluminium dish Material weighing plate: Overall dimensions mounted 240 x 365 x 180 mm (WxDxH):

Revolving screw feet: yes Weighing surface (d): 92

Piktogramme

STANDARD

















1

OPTION

