
KERN TGD50-3CS05







Measuring system	
Adjustment options:	External calibration
Eccentric loading at 1/3 [Max]:	5 mg
Linearity:	3 mg
Readability [d]:	1 mg
Recommended adjusting weight:	50 g (F2)
Repeatability:	3 mg
Resolution:	50000
Stabilisation time under laboratory conditions:	3 s
Tare range:	50 g
Warm up time:	2 h
Weighing capacity [Max]:	50 g
Weighing system:	Strain gauge
Weighing units:	dwt ct gn oz ozt g

Display	
Display digit height (large):	2 cm
Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	35 °C
Minimum ambient temperature:	5°C
Minimum humidity:	15 %

Power supply	
Battery:	4x1.5 V AAA
Operating time:	150 h

Services (optional)

Adjustment at the location of installation: 961-247

DAkkS Certificate: 963-127

Category **KERN** Brand: Product Group: Pocket balance

Packaging & shipping 24 h Delivery: Gross weight: 2,215 kg Net weight: 980 g Shipping method: Parcel service

Construction	
Casing material:	Plastic
Dimensions housing (WxDxH):	96 x 149 x 36 mm
Level indicator:	yes
Material weighing plate:	stainless steel
Revolving screw feet:	yes
Weighing surface (d):	65

Piktogramme

STANDARD











