KERN CFS 300-3



Professional, high-resolution counting balance with 100 item memories and second balance interface, counting resolution up to 75,000 points



Measuring system	
Adjustment options:	External calibration
Linearity:	4 mg
Readability [d]:	1 mg
Recommended adjusting weight:	200 g (F1); 100 g (F1)
Repeatability:	2 mg
Resolution:	300000
Stabilisation time under laboratory conditions:	2 \$
Tare range:	300 g
Warm up time:	2 h
Weighing capacity [Max]:	300 g
Weighing system:	Strain gauge
Weighing units:	g
Display	
Display digit height (large):	2 cm
Counting	
Counting resolution:	60000
Mininum piece weight at piece counting (Laboratory:	5 mg
Mininum piece weight at piece counting (Normal):	50 mg
Reference weight:	yes
Functions	
Conversion function:	yes
Counting function:	yes
Function to save totals:	yes
PRE-TARE function:	yes
Weighing with tolerance range:	yes

Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	0°C
Minimum humidity:	0 %
Power supply	
Charging time:	14 h
Input voltage:	110 V - 230 V AC
Mains adapter:	Mains adapter external
Mains adapter/adapter included:	UK US EURO CH
Operating time (Backlight off):	70 h
Operating time (Backlight on):	40 h
Rechargeable battery:	Rchrg. battery optional
. teerrange above battery.	Trom groundry opnional
Services (optional)	
DAkkS Certificate:	963-127
Category	
Brand:	KERN
Category:	Balances
Product Group:	Counting scale
Packaging & shipping	
	24 h
Delivery:	24 h 630 x 545 x 225 mm
Delivery: Dimensions packaging (WxDxH):	630 x 545 x 225 mm
Delivery: Dimensions packaging (WxDxH): Gross weight:	630 x 545 x 225 mm 5,500 kg
Delivery: Dimensions packaging (WxDxH):	630 x 545 x 225 mm
Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method:	630 x 545 x 225 mm 5,500 kg 2,500 kg
Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction	630 x 545 x 225 mm 5,500 kg 2,500 kg Parcel service
Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Casing material:	630 x 545 x 225 mm 5,500 kg 2,500 kg Parcel service
Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Casing material: Dimensions device (WxDxH):	630 x 545 x 225 mm 5,500 kg 2,500 kg Parcel service Plastic 320 x 350 x 125 mm
Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Casing material: Dimensions device (WxDxH): Dimensions draft shield (WxDxH):	630 x 545 x 225 mm 5,500 kg 2,500 kg Parcel service Plastic 320 x 350 x 125 mm 167 x 154 x 80 mm
Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Casing material: Dimensions device (WxDxH): Dimensions draft shield (WxDxH): Dimensions housing (WxDxH):	630 x 545 x 225 mm 5,500 kg 2,500 kg Parcel service Plastic 320 x 350 x 125 mm 167 x 154 x 80 mm 315 x 350 x 180 mm
Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Casing material: Dimensions device (WxDxH): Dimensions draft shield (WxDxH):	630 x 545 x 225 mm 5,500 kg 2,500 kg Parcel service Plastic 320 x 350 x 125 mm 167 x 154 x 80 mm
Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Casing material: Dimensions device (WxDxH): Dimensions draft shield (WxDxH): Dimensions of display device	630 x 545 x 225 mm 5,500 kg 2,500 kg Parcel service Plastic 320 x 350 x 125 mm 167 x 154 x 80 mm 315 x 350 x 180 mm
Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Casing material: Dimensions device (WxDxH): Dimensions draft shield (WxDxH): Dimensions of display device (WxDxH):	630 x 545 x 225 mm 5,500 kg 2,500 kg Parcel service Plastic 320 x 350 x 125 mm 167 x 154 x 80 mm 315 x 350 x 180 mm 320 x 350 x 120 mm
Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Casing material: Dimensions device (WxDxH): Dimensions draft shield (WxDxH): Dimensions of display device (WxDxH): Level indicator:	630 x 545 x 225 mm 5,500 kg 2,500 kg Parcel service Plastic 320 x 350 x 125 mm 167 x 154 x 80 mm 315 x 350 x 180 mm 320 x 350 x 120 mm
Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Casing material: Dimensions device (WxDxH): Dimensions draft shield (WxDxH): Dimensions of display device (WxDxH): Level indicator: Material weighing plate: Overall dimensions mounted	630 x 545 x 225 mm 5,500 kg 2,500 kg Parcel service Plastic 320 x 350 x 125 mm 167 x 154 x 80 mm 315 x 350 x 180 mm 320 x 350 x 120 mm yes stainless steel
Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Casing material: Dimensions device (WxDxH): Dimensions draft shield (WxDxH): Dimensions of display device (WxDxH): Level indicator: Material weighing plate: Overall dimensions mounted (WxDxH):	630 x 545 x 225 mm 5,500 kg 2,500 kg Parcel service Plastic 320 x 350 x 125 mm 167 x 154 x 80 mm 315 x 350 x 180 mm 320 x 350 x 120 mm yes stainless steel 315 x 350 x 180 mm
Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Casing material: Dimensions device (WxDxH): Dimensions draft shield (WxDxH): Dimensions of display device (WxDxH): Level indicator: Material weighing plate: Overall dimensions mounted (WxDxH): Revolving screw feet: Weighing space (WxDxH):	630 x 545 x 225 mm 5,500 kg 2,500 kg Parcel service Plastic 320 x 350 x 125 mm 167 x 154 x 80 mm 315 x 350 x 180 mm 320 x 350 x 120 mm yes stainless steel 315 x 350 x 180 mm
Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Casing material: Dimensions device (WxDxH): Dimensions draft shield (WxDxH): Dimensions of display device (WxDxH): Level indicator: Material weighing plate: Overall dimensions mounted (WxDxH): Revolving screw feet:	630 x 545 x 225 mm 5,500 kg 2,500 kg Parcel service Plastic 320 x 350 x 125 mm 167 x 154 x 80 mm 315 x 350 x 180 mm 320 x 350 x 120 mm yes stainless steel 315 x 350 x 180 mm yes 158 x 143 x 64 mm

KERN CFS 300-3



Professional, high-resolution counting balance with 100 item memories and second balance interface, counting resolution up to 75,000 points

Piktogramme STANDARD LALEXT MEMORY RS 232 DUAL SUM TOL MULTI DMS 1 DAY OPTION DAKKS ACCU +3 DAYS FACTORY