

LCB 50

Portable calibration bath with temperature range of 30°C .. 225°C. Which offers an immersion depth of 190 mm and a diameter of 60mm, allowing a higher range. Leyro Instruments offer the best calibration bath performance for the most demanding accurate calibrations. Thanks to adjustable magnetic stirrer with potentiometer, can homogenize the calibration area, which makes it one of the most reliable equipment thanks to its high stability of 0.03°C and excellent uniformity 0,05°C.



APPLICATIONS Calibration Laboratories Testing Labs Universities / R & D Chemical / Pharmaceutical Industry Food industry

> HIGHLIGHTS Temperature range 30 ... 225°C Immersion depth 190mm Stability 0,03°C Uniformity 0,05°C Fast response time

CE

General information

PID temperature controller

Keyboard Selection of set point values alert / security and menu

Adjustable speed magnetic stirrer by potentiometer

High temperature stability up to ± 0.03°C

Lower temperature uniformity of ± 0.05°C

Integrated Pt100 sensor for reference temperature measurements

Temperature chamber with basket for temperature sensors to be calibrated.





Technical data

Operating temperature range (°C)
Temperature stability (°C)
Uniformity
Resolution
Well Diameter
Immersion depth
Well capacity
Warm-up time
Cooling time
Housing and assembly
Dimensions An x La x Al (cm)
Weight (kg)
Supply

30 ... 225 °C ±0.05 °C 0.03°C 0.1°C 60 mm 190 mm 0.7 litters 25 to 220°C: 42 Minutes 220 to 100°C: 35 Minutes Desktop / portable 190 x 270 x 428 9.6 kg 110 ... 230 Vac 50/60 Hz



Scope of delivery

Basic instrument LBC 50 Teflon magnetic stirrer; basket; 1,5 m power cord cable and metal lid Drain Pump Traceable Certificate 3.1 (5 Points of calibration) English manual

Optional

Comunications RS 485 Magnetic stirrer Methacrylate lid with 6 inserts. Trolley transport case with wheels and handle. ENAC / ISO 17025 calibration certificate

> Importør: Impex Produkter AS Gamle Drammensvei 107 1363 Høvik www.impex.no info@impex.no Tel.: 22 32 77 20