KERN **EOC 60K-3**

Robust and high-resolution platform scale with practical Flip/Flop display device for greatest ease of use

Measuring system

Adjustment options:	External calibration
Linearisation (points):	3
Linearity:	3 g | 6 g
Load cell connection:	4-wire
Readability [d]:	1 g | 2 g
Recommended adjusting weight:	60 kg (F2)
Repeatability:	1 g | 2 g
Resolution:	30 30.000
Stabilisation time under laboratory conditions:	2 s
Tare range:	60 kg
Warm up time:	2 h
Weighing capacity [Max]:	30 kg | 60 kg
Weighing system:	Strain gauge
Weighing units:	oz kg PCS g lb

Display

Display digit height (large):	2,500 cm
Display digit height (small):	2,500 cm

Counting

Counting resolution:	30000
Mininum piece weight at piece counting (Laboratory:	2 g
Mininum piece weight at piece counting (Normal):	20 g

Functions

Counting function:	yes
Percentage determination:	yes
Vibration-free weighing (Animal weighing program):	yes
Weighing with tolerance range:	yes

Environmental conditions

Maximum humidity:	80 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	-10 °C
Minimum humidity:	0 %

Power supply

Charging time:	3 h
Input voltage:	100V-240V 0.4A
Mains adapter:	Mains adapter external
Mains adapter/adapter included:	CH UK EURO
Operating time:	100 h
Operating time (Backlight off):	43 h
Operating time (Backlight on):	26 h
Rechargeable battery:	Rchrg. battery optional - intern

Services (optional)

Adjustment at the location of installation:	961-249
DAkkS Certificate:	963-129

Category

Brand:	KERN
Category:	Balances
Product Group:	Industiral scale

Packaging & shipping

Delivery:	24 h
Dimensions packaging (WxDxH):	560 x 400 x 160 mm
Gross weight:	7,500 kg
Net weight:	5,200 kg
Shipping method:	Parcel service

Construction

|	
Cable length of display device:	3 m
Dimensions of display device (WxDxH):	268 x 115 x 80 mm
Dimensions of weighing plate (WxDxH):	300 x 300 x 110 mm
of stand:	33 cm
Level indicator:	yes
Material weighing plate:	stainless steel
Revolving screw feet:	yes
Wall mount:	yes

KERN **EOC 60K-3**

Robust and high-resolution platform scale with practical Flip/Flop display device for greatest ease of use

Piktogramme

STANDARD

| CAL EXT | RS 232 | KCP PROTOCOL | GLP PRINTER | PCS | SUM | PERCENT | TOL | MOVE |
| IP 65 | MULTI | DMS | 1 DAY | | | | | |

OPTION

| ACCU | DAkkS +3 DAYS |